



Dahua Technology IPC- HFW2849TL-S- LED-0280B-PRO - fixed-focus bullet network camera with WizSense technology

Model: IPC-HFW2849TL-S-LED-0280B-PRO

Manufacturer: DAHUA

EAN: 6939554956478

Product Code: 418798

R3,558

Certification: CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU | Voice codecs: PCM | Camera shutter speed: 1/3 - 1/100000 s | Voice codecs: G.711a | Voice codecs: G.726 | Camera shutter type: Electronic | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Pan range: 0 - 360° | Voice codecs: G.711Mu | Mirror: Yes | Total megapixels: 8 MP | Noise reduction technology: 3D noise reduction | Placement supported: Indoor & outdoor | Number of users: 20 user(s) | Video motion detection: Yes | Built-in HDD: No | Video compression formats:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

H.264H | Frame rate: 30 fps | Progressive scan: Yes | Video compression formats: MJPEG | RAM capacity: 256 MB | Video compression formats: H.265 | Video compression formats: H.264B | Day/night mode: Yes | Sensor type: CMOS | Video compression formats: H.264 | Power consumption (Power over Ethernet (PoE)): 3.2 W | Mounting type: Ceiling/Wall/Pole | Night vision: Yes | Region of Interest (ROI) encoding: Yes | Mobile operating systems supported: iOS | Management software: Smart PSS Lite DSS DMSS | Number of lenses: 3 | ROM capacity: 128 MB | Mobile operating systems supported: Android | Weight: 570 g | Power source type: DC, PoE | Operating temperature (T-T): -40 - 60 °C | Wide Dynamic Range (WDR): Yes | Networking standards: IEEE 802.3af | Highlight Compensation (HLC): Yes | Bit rate: H.264: 32 kbps-8192 kbps H.265: 12 kbps-8192 kbps | White balance: Street lamp | Housing material: Metal | White balance: Auto | Number of illumination LEDs: 4 | Form factor: Bullet | White balance: Manual | Product colour: White | Storage temperature (T-T): -40 - 60 °C | White balance: Custom modes | Maximum resolution: 3840 x 2160 pixels | White balance: Outdoor | Ethernet LAN (RJ-45) ports: 1 | Height: 76.2 mm | Number of cameras: 1 | International Protection (IP) code: IP67 | Night vision distance: 50 m | Power consumption (max): 6.1 W | Operating relative humidity (H-H): 0 - 95% | Type: IP security camera | White balance: Natural | Angle of rotation: 360° | Tilt angle range: 0 - 90° | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 2688 x 1520 | Supported graphics resolutions: 1920 x 1080 | Supported graphics resolutions: 3072 x 1728 | Supported graphics resolutions: 2048 x 1536 | Supported graphics resolutions: 3840 x 2160 | Supported graphics resolutions: 352 x 288 | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 1280 x 960 | Depth: 197.9 mm | Power consumption (typical): 2.3 W | Supported graphics resolutions: 1280 x 720 | Supported graphics resolutions: 2880 x 1620 | Supported graphics resolutions: 2304 x 1296 | Supported graphics resolutions: 640 x 480 | Supported graphics resolutions: 3072 x 2048 | Connectivity technology: Wired | Supported network protocols: IPv4 IPv6 HTTP TCP UDP ARP RTP RTSP RTCP RTMP SMTP FTP SFTP DHCP DNS DDNS QoS UPnP NTP Multicast ICMP IGMP NFS PPPoE P2P Bonjour Auto Registration | Width: 80.2 mm | Built-in light: Yes | Number of Privacy masking areas: 4 | Max power consumption (Power over Ethernet (PoE)) : 7,4 W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950