



Dahua Technology IPC- HDW2849T-S- LED-0280B-PRO



Model: HDW2849T-S-LED-0280B-PRO

Manufacturer: DAHUA

EAN: 6939554956430

Product Code: 418799

R3,729

Certification: ONVIF (Profile S/G/T) | Operating temperature (T-T): -40 - 60 °C | Product colour: White | Maximum resolution: 3840 x 2160 pixels | Bit rate: H.264: 32 kbps-8192 kbps H.265: 12 kbps-8192 kbps | Power consumption (typical): 2.4 W | Depth: 110 mm | Connectivity technology: Wired | Supported graphics resolutions: 352 x 288 | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 2304 x 1296 | Housing material: Metal | Weight: 420 g | Supported graphics resolutions: 3840 x 2160 | Supported graphics resolutions: 2592 x 1944 | International Protection (IP) code: IP67 | Number of cameras: 1 | Wide Dynamic Range (WDR): Yes | Supported graphics resolutions: 1280 x 720 | White balance: Street lamp | White balance: Manual | White balance: Auto | White balance: Outdoor | Supported network protocols: IPv4 IPv6 HTTP TCP UDP ARP RTP RTSP RTCP RTMP SMTP FTP SFTP DHCP DNS DDNS QoS UPnP NTP Multicast ICMP IGMP NFS PPPoE P2P Bonjour Auto Registration | White balance: Regional custom | Supported graphics resolutions: 2688 x 1520 | Supported graphics resolutions: 1920 x 1080

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

| Networking standards: IEEE 802.3af | Type: IP security camera | White balance: Natural | Highlight Compensation (HLC): Yes | Angle of rotation: 270° | Form factor: Dome | Total megapixels: 8 MP | Number of illumination LEDs: 2 | Operating relative humidity (H-H): 0 - 95% | Built-in light: Yes | Power consumption (max): 6.4 W | Width: 110 mm | Supported graphics resolutions: 704 x 576 | Ethernet LAN (RJ-45) ports: 1 | Night vision distance: 20 m | Height: 110 mm | Power source type: DC, PoE | Mirror: Yes | Mobile operating systems supported: Android | Video motion detection: Yes | Video compression formats: H.265 | Day/night mode: Yes | Built-in HDD: No | Mounting type: Ceiling/Wall/Pole | Power consumption (Power over Ethernet (PoE)): 3 W | Number of Privacy masking areas: 4 | Region of Interest (ROI) encoding: Yes | Camera shutter type: Mechanical | Camera shutter type: Auto | Voice codecs: PCM | Management software: Smart PSS Lite DSS DMSS | Night vision: Yes | Number of users: 20 user(s) | Camera shutter speed: 1/3 - 1/100000 s | Video compression formats: MJPEG | Mobile operating systems supported: iOS | Video compression formats: H.264B | Video compression formats: H.264H | Video compression formats: H.264 | Progressive scan: Yes | Sensor type: CMOS | Voice codecs: G.711a | Voice codecs: G.726 | Voice codecs: G.711Mu | Noise reduction technology: 3D noise reduction | Placement supported: Indoor & outdoor

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950