



EZVIZ H6c Pro 2K camera



Model: 303103081

Manufacturer: EZVIZ

EAN: 6941545632667

Product Code: 418815

R1,180

Storage relative humidity (H-H): 0 - 95% | Ethernet LAN (RJ-45) ports: 1 | Operating temperature (T-T): -10 - 50 °C | Type: IP security camera | Product colour: White | Reset button: Yes | Connectivity technology: Wired | User access level: Administrator, Operator, User | Form factor: Dome | Number of cameras: 1 | Ethernet interface type: Fast Ethernet | Ethernet interface type: 1 Gigabit Ethernet | Storage temperature (T-T): -10 - 50 °C | Ethernet LAN: Yes | Ethernet interface type: 25 Gigabit Ethernet | Operating relative humidity (H-H): 0 - 95% | Ethernet interface type: 100 Gigabit Ethernet | Ethernet interface type: 1000 Gigabit Ethernet | Ethernet interface type: 2x 1 Gigabit Ethernet | Ethernet interface type: Fast Ethernet, Gigabit Ethernet | Ethernet interface type: 1.25 Gigabit Ethernet | Ethernet interface type: 10 Megabit Ethernet | Ethernet interface type: 100 Megabit Ethernet | Ethernet interface type: 5 Gigabit Ethernet | Ethernet interface type: 40 Gigabit Ethernet | Ethernet interface type: 10 Gigabit | Ethernet interface type: 10 Gigabit Ethernet, Gigabit Ethernet | Wi-Fi: No | Maximum resolution: 2304 x 1296 pixels | Ethernet interface type: Gigabit Ethernet | Ethernet interface type: 10 Gigabit Ethernet, Fast Ethernet, Gigabit Ethernet | Ethernet interface type: 10 Gigabit Ethernet | Ethernet interface type: 2.5 Gigabit Ethernet | Ethernet interface type: 16

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Gigabit Ethernet | Sustainability compliance: Yes | Power source type: DC, PoE | Audio formats supported: PCM | Audio formats supported: AAC-LC | Audio formats supported: G.711 A-law | Camera shutter speed: 1/3 - 1/100000 s | Audio formats supported: G.726 | Audio formats supported: MP2L2 | Audio formats supported: G.711 μ -law | Live view: Yes | Audio formats supported: G.722.1 | Sensor type: CMOS | Built-in HDD: No | Minimum illumination: 0 lx | Day/night mode: Yes | Mounting type: Ceiling/Pole | Placement supported: Outdoor | Compliance certificates: BIS | Compliance certificates: CB | Compliance certificates: UL | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Industry Canada (IC) | Compliance certificates: KC

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950