



IP camera Hikvision DS- 2CD1343G2- LIU(2.8mm)

Model: DS-2CD1343G2-LIU

Manufacturer: HIKVISION

EAN: 6942160472737

Product Code: 418839

R2,420

Certification: FCC: 47 CFR Part 15, Subpart B, EN 55032: 2015, EN 61000-3-2:2019, EN 61000-3-3: 2013+A1:2019, EN 50130-4: 2011 +A1: 2014, RCM: AS/NZS CISPR 32: 2015, IC: ICES-003: Issue 7, UL 62368-1, IEC 62368-1: 2014+A11, CE-LVD: EN 62368-1: 2014/A11: 2017, IS 13252 (Part 1): 2010/IEC 60950-1: 2005, CE-RoHS: 2011/65/EU, WEEE: 2012/19/EU, Reach: Regulation (EC) No 1907/2006 | Supported graphics resolutions: 640 x 360 | Video streaming: Yes | Supported graphics resolutions: 640 x 480 (VGA) | Pan range: 0 - 360° | Video compression formats: H.265+ | Dedicated application: Hik-Connect (Android, iOS) | Image quality adjustment: Sharpness | Image quality adjustment: Brightness | Viewing angle, diagonal: 114° | Image quality adjustment: White balance | Tilt angle range: 0 - 75° | Maximum resolution: 2560 x 1440 pixels | Camera tilt control: Yes | Image quality adjustment: Saturation | Region of Interest (ROI) encoding: Yes | Gain control type: Auto | Heartbeat: Yes | Bit rate: 32 Kbps - 8 Mbps | Video compression formats: M-JPEG | Image quality adjustment: Contrast | Night vision distance: 30 m | Total megapixels: 4 MP | Number of lenses: 1 | Camera shutter speed: 1/3 - 1/100000 s | Operating temperature (T-T): -30 - 60 °C | Optical sensor size: 25.4 / 3 mm (1 / 3") | Sensor type: CMOS | Progressive scan: Yes | Password protection: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Mirror: Yes | Built-in microphone: Yes | Noise reduction technology: 3D noise reduction | Storage temperature (T-T): -30 - 60 °C | Package width: 150 mm | Package height: 141 mm | Quality of Service (QoS) support: Yes | Package depth: 150 mm | Power consumption (Power over Ethernet (PoE)): 6.5 W | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 2560 x 1440 | Form factor: Turret | Infrared (IR) cut-off filter: Yes | Camera pan control: Yes | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Ethernet LAN: Yes | Angle of rotation: 360° | Power source type: DC, PoE | Noise reduction: Yes | Video compression formats: H.265 | Bluetooth: No | Video compression formats: H.264 | DC output voltage: 12 | DC output current: 0.4 A | Day/night mode: Yes | Video compression formats: H.264+ | Digital watermark: Yes | Maximum aperture number: 1.6 | Number of sensors: 1 | Infra-red wavelength: 850 nm | Product colour: White | Mounting type: Ceiling/wall | Fixed focal length: 2.8 mm | Night vision: Yes | Video motion detection: Yes | Privacy masking: Yes | Number of cameras: 1 | Frame rate: 20 fps | Viewing angle, vertical: 54° | Number of users: 32 user(s) | LED type: IR | Power consumption (max): 5 W | Diameter: 11 cm | Weight: 340 g | Viewing angle, horizontal: 98° | Wide Dynamic Range (WDR): Yes | Package weight: 560 g | Height: 89.2 mm | Placement supported: Outdoor | Wi-Fi: No | Ethernet LAN (RJ-45) ports: 1 | Operating relative humidity (H-H): 0 - 95% | International Protection (IP) code: IP67 | Built-in HDD: No | Networking standards: IEEE 802.3af | Housing material: Metal | Storage relative humidity (H-H): 0 - 95% | Type: IP security camera | Web-based management: Yes | Housing material: Plastic | Connectivity technology: Wired

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950