



HIKVISION DS-2CD1061G2-LIU 2.8mm IP CAMERA



Model: DS-2CD1061G2-LIU 2.8mm PL

Manufacturer: HIKVISION

EAN: 6936422131029

Product Code: 418844

R2,050

Number of Privacy masking areas: 4 | Connectivity technology: Wired | Package height: 118 mm | Built-in light: Yes | Supported graphics resolutions: 3200 x 1800 | Pan range: 0 - 360° | Width: 66 mm | Audit log: Yes | Supported graphics resolutions: 640 x 360 | Protection features: Waterproof | Supported graphics resolutions: 1280 x 720 (HD 720) | Package weight: 481 g | Signal-to-Noise Ratio (SNR): 52 dB | Supported graphics resolutions: 2688 x 1520 | Bit rate range: 16 - 160 Kbit/s | Client interoperability: iVMS-4200, Hik-Connect | Total megapixels: 6 MP | Camera shutter speed: 1 - 1/100000 s | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 640 x 480 (VGA) | Length: 170.8 mm | Number of cameras: 1 | Minimum illumination: 0 lx | Progressive scan: Yes | Operating temperature (T-T): -30 - 60 °C | Bluetooth: No | Package width: 216 mm | Built-in microphone: Yes | Power source type: DC, PoE | Storage temperature (T-T): -30 - 60 °C | Supported network protocols: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP | Audio formats supported: MP2L2 | Ethernet LAN: Yes | Angle of rotation: 360° | Audio formats supported: PCM | Audio formats supported: G.726 | Audio formats supported: AAC-LC | Audio formats supported: G.711 | Package

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

depth: 121 mm | Audio formats supported: G.722.1 | Product colour: White | Wide Dynamic Range (WDR): Yes | Tilt angle range: 0 - 90° | Night vision distance: 30 m | Ethernet interface type: Fast Ethernet | Highlight Compensation (HLC): Yes | Form factor: Bullet | Bit rate: 32 Kbps - 16 Mbps | Digest authentication: Yes | Power consumption (max): 5 W | Maximum resolution: 3200 x 1800 pixels | Fixed focus: Yes | Built-in HDD: No | International Protection (IP) code: IP67 | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Height: 69.1 mm | Privacy protection: Yes | Ethernet LAN (RJ-45) ports: 1 | Back Light Compensation (BLC): Yes | Weight: 285 g | Wi-Fi: No | Operating relative humidity (H-H): 0 - 95% | Sample rates: 8 - 16 kHz | Housing material: Plastic | Housing material: Metal | Type: IP security camera | Web-based management: Yes | Storage relative humidity (H-H): 0 - 95% | Number of languages: 1 | Detect distance: 76 m | Infra-red wavelength: 850 nm | Image quality adjustment: White balance | Image quality adjustment: Sharpness | Sensor type: CMOS | Number of lenses: 1 | DC output current: 0.41 A | Image quality adjustment: Saturation | Image quality adjustment: Contrast | Languages support: Polish | Compliance certificates: WEEE | Compliance certificates: RCM | Compliance certificates: REACH | Night vision: Yes | Compliance certificates: CB | Compliance certificates: RoHS | Compliance certificates: CE | Infrared (IR) cut-off filter: Yes | Recognize distance: 15 m | Heartbeat: Yes | Video streaming: Yes | Mirror: Yes | Image quality adjustment: Brightness | Placement supported: Indoor & outdoor | Compliance certificates: Low Voltage Directive (LVD) | Fixed focal length: 2.8 mm | DC output voltage: 12 | Number of users: 32 user(s) | Password reset via email: Yes | Video motion detection: Yes | Privacy masking: Yes | Password protection: Yes | Video compression formats: H.264+ | Digital watermark: Yes | Video compression formats: H.264 | Region of Interest (ROI) encoding: Yes | Live view: Yes | Day/night mode: Yes | Video compression formats: M-JPEG | Maximum aperture number: 1.6 | Video compression formats: H.265+ | Lens viewing angle, vertical: 55° | Observe distance: 30 m | Number of sensors: 1 | Sustainability compliance: Yes | Power consumption (Power over Ethernet (PoE)): 6.5 W | Mounting type: Ceiling/wall | Lens viewing angle, diagonal: 127° | Dynamic range: 120 dB | Identify distance: 7 m | Video compression formats: H.265 | Lens viewing angle, horizontal: 105° | User access level: Administrator, Operator, User | Number of simultaneous live view channels: 6 channels

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950