



Hikvision DS-7632NXI-K2(D) network video recorder 1U Black



Model: DS-7632NXI-K2(D)

Manufacturer: HIKVISION

EAN: 6942160489759

Product Code: 418846

R5,411

Supported resolutions: 12 MP/8 MP/6 MP/5 MP/4 MP/3

MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF | VGA (D-Sub) output ports: 1 | DC-in jack: Yes |

Video input channels: 32 channels | Output voltage: 12 V | Ethernet LAN data rates: 100 | Ethernet

LAN data rates: 1000 Mbit/s | Video formats supported: H.265+ | Input bandwidth: 256 Mbit/s |

Height: 52 mm | Rack capacity: 1U | Video formats supported: H.264+ | Brand compatibility:

Hikvision Digital Technology | HDD interface: SATA | Video formats supported: H.264 | Ethernet LAN

data rates: 10 | Internal SATA ports quantity: 2 | Video formats supported: H.265 | Number of

simultaneously played channels: 16 channels | Product colour: Black | Power over Ethernet

(PoE): Yes | Number of HDDs supported: 2 | Built-in processor: No | Width: 385 mm | Rack mounting:

Yes | Supported network protocols: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP,

SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS | Maximum resolution: 3840 x 2160 pixels | Built-in

display: No | HDMI ports quantity: 1 | Maximum storage capacity: 10 TB | On/off switch: Yes | Audio

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

formats supported: AAC | Alarm input channels: 4 | Face detection: Yes | Power consumption (max): 15 W | Output bandwidth: 160 Mbit/s | Audio RCA inputs: 1 | Weight: 1 kg | Maximum frame rate: 30 fps | HDMI output: Yes | Audio RCA outputs: 1 | Alarm output channels: 1 | Audio formats supported: G.711 μ -law | Audio formats supported: G.722 | Operating temperature (T-T): -10 - 55 °C | USB 2.0 ports quantity: 2 | Depth: 315 mm | Audio formats supported: G.711 A-law | Wi-Fi: No | Operating relative humidity (H-H): 10 - 90% | Output current: 3.3 A | Ethernet LAN (RJ-45) ports: 1 | Audio formats supported: G.726 | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950