



REOLINK TrackMix W760 8MP WLAN- Auen-IP-Kamera mit zwei Objektiven



Model: W760

Manufacturer: REOLINK

EAN: 6978285032556

Product Code: 418894

R4,959

Packaging content: 1* Trackmix Series W760 1* Mounting Template 1* Waterproof Lid 1* Power Adapter 1* 1m Network Cable 1* 4.5m Power Extension Cable 1* Surveillance Sticker 1* Quick Start Guide 1* Pack of Screws | Lens viewing angle, horizontal: 38 - 104° | Video motion detection: Yes | Lens viewing angle, vertical: 21 - 60° | Camera tilt control: Yes | Ethernet LAN (RJ-45) ports: 1 | Operating temperature (T-T): -10 - 55 °C | Built-in speaker(s): Yes | Video streaming: Yes | User access level: Administrator, User | Camera pan control: Yes | Mounting type: Wall | Placement supported: Outdoor | Infrared (IR) cut-off filter: Yes | Virtual assistant: Google Assistant | Maximum aperture number: 1.6 | Number of users: 20 user(s) | Auto-tracking: Yes | Day/night mode: Yes | Video compression formats: H.265 | Connectivity technology: Wireless | Video recording: Yes | Infra-red wavelength: 850 nm | Bluetooth: No | Video compression formats: H.264 | Live view: Yes | DC-in jack: Yes | LED type: IR/White | Wi-Fi standards: 802.11g | Reset button: Yes | Wi-Fi: Yes | Night

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

vision: Yes | Wi-Fi standards: 802.11a | Number of lenses: 1 | Supported video modes: 2160p | Bit rate: 128Kbps - 8192Kbps | Wi-Fi standards: Wi-Fi 4 (802.11n) | Maximum resolution: 3840 x 2160 pixels | Antenna type: External | Weight: 1.21 kg | Built-in HDD: No | Wi-Fi standards: 802.11b | Maximum memory card size: 256 GB | Mounting kit: Yes | Form factor: Turret | Number of cameras: 1 | Antennas quantity: 2 | Audio system: 2-way | International Protection (IP) code: IP65 | Mobile operating systems supported: iOS | Card reader integrated: Yes | Mobile operating systems supported: Android | Frame rate: 25 fps | Fixed focal length: 2.8 mm | Tilt speed: 1.5 °/sec | DC output current: 1 A | Total megapixels: 8 MP | Optical sensor size: 25.4 / 3 mm (1 / 3") | Networking standards: IEEE 802.11a | Video formats supported: H.265 | Manual: Yes | Mac operating systems supported: Yes | Operating relative humidity (H-H): 10 - 90% | Ethernet interface type: Fast Ethernet | Windows operating systems supported: Yes | Compatible memory cards: MicroSD (TransFlash) | Security algorithms: WPA2-PSK | DC output voltage: 12 | Security algorithms: WPA-PSK | Pan range: 0 - 355° | Width: 147 mm | Night vision distance: 30 m | Type: IP security camera | Supported graphics resolutions: 3840 x 2160 | Zoom capability: Yes | Height: 129 mm | Video formats supported: H.264 | Number of illumination LEDs: 2 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Pan speed: 90 °/sec | Ethernet LAN: Yes | Product colour: White | Sensor type: CMOS | Built-in microphone: Yes | Power source type: DC | Screws included: Yes | Networking standards: IEEE 802.11b | Tilt angle range: 0 - 90° | Depth: 228 mm | Supported network protocols: HTTP, HTTPS, SSL, TCP/IP, UDP, UPNP, RTSP,RTMP, SMTP, ONVIF, NTP, DHCP, DNS, DDNS, P2P | Human and vehicle targets classification: Yes | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Warnings: The product contains electronic components do not dispose of with the normal household waste.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950