



TP-Link Outdoor Pan/Tilt Security Wi-Fi Camera SPEC: 3K 5MP (2880x1620), 2.4 GHz, 2 External Antennas, 1 Ethernet Port, Horizontal 360



Model: Tapo C530WS

Manufacturer: TP-LINK

EAN: 8885020624984

Product Code: 418902

R1,965

Tilt angle range: 60 - 130° | Bluetooth: No | AC input voltage: 100 - 240 V | Audio output channels: 1.0 channels | Product colour: White | Antenna type: External | AC input frequency: 50/60 Hz | Reset button: Yes | Connectivity technology: Wired & Wireless | Sensor type (panoramic camera): CMOS | Networking standards: IEEE 802.11ax | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Mounting type: Wall | Live view: Yes | Number

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

of microphones: 1 | Auto pan mode: Yes | Image quality adjustment: DNR | Motion sensor: Yes | Alert notification type: Push notification | Maximum operating distance: 29.9 m | Placement supported: Outdoor | Remote viewing: Yes | Built-in speaker(s): Yes | Night vision: Yes | Mirror: Yes | Mounting brackets included: Yes | Video motion detection: Yes | HTTPS encryption: Yes | Width: 123.8 mm | Video recording: Yes | Supported graphics resolutions: 2880 x 1620 | Package weight: 710 g | Compatible memory cards: MicroSD (TransFlash) | Housing material: Metal | Antennas quantity: 2 | Audio formats supported: RTSP | Remotely operated: Yes | Weatherproof: Yes | Built-in siren: Yes | Frame rate: 30 fps | Depth: 90 mm | Camera tilt control: Yes | Package depth: 210 mm | Lens viewing angle, diagonal: 112° | Protection features: Waterproof | Operating temperature (T-T): -30 - 60 °C | Form factor: Turret | Wi-Fi standards: 802.11g | LED type: IR/White | Sensor type: CMOS | Wi-Fi standards: Wi-Fi 4 (802.11n) | Height: 123 mm | Storage temperature (T-T): -40 - 60 °C | Ethernet LAN: Yes | Lens viewing angle, horizontal: 95° | Type: IP security camera | Wi-Fi standards: 802.11b | Focal length range: 3.2 mm | DC output voltage: 9 | Wi-Fi: Yes | Maximum resolution: 2880 x 1620 pixels | Progressive scan: Yes | Audio detection: Yes | Storage relative humidity (H-H): 0 - 90% | Package width: 160 mm | Camera pan control: Yes | Cloud-managed: Yes | Video compression formats: H.264 | International Protection (IP) code: IP66 | Lens viewing angle, vertical: 53° | Day/night mode: Yes | Audio system: 2-way | Optical sensor size: 25.4 / 3 mm (1 / 3") | Power source type: AC, DC | Total megapixels: 5 MP | Number of cameras: 1 | Siren noise level: 99 dB | Drilling template included: Yes | Ethernet LAN (RJ-45) ports: 1 | Audio input channels: 1.0 channels | Manual: Yes | Operating relative humidity (H-H): 10 - 90% | DC output current: 0.85 A | Digital zoom: 12x | Mounting kit: Yes | Package type: Box | Maximum memory card size: 512 GB | Built-in microphone: Yes | Screws included: Yes | Package height: 145 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950