

TP-Link Tapo C202 Spherical IP security camera Indoor 1920 x 1080 pixels Ceiling/Desk

Model: Tapo C202

Manufacturer: TP-LINK

EAN: 8885020621051

Product Code: 418910

R1,238

Cables included: AC | Wi-Fi standards: 802.11g | Reset button: Yes | Connectivity technology: Wired & Wireless | Product colour: White | Wi-Fi standards: 802.11b | Wi-Fi standards: Wi-Fi 4 (802.11n) | Storage temperature (T-T): -40 - 70 °C | Compatible memory cards: MicroSD (TransFlash) | Height: 112.6 mm | Video compression formats: H.264 | Storage relative humidity (H-H): 5 - 90% | Maximum resolution: 1920 x 1080 pixels | Wi-Fi: Yes | AC input voltage: 100-240 V | USB port: No | Mounting type: Desk/Ceiling | LED type: 1 IR LED | Built-in HDD: No | Security algorithms: WPA2 | Wide Dynamic Range (WDR): Yes | Built-in light: Yes | Frame rate: 15 fps | Optical sensor size: 25.4 / 3 mm (1 / 3") | Intelligent Video Surveillance (IVS) system features: Human detection | Audio system: 2-way | Maximum aperture number: 2.4 | Maximum memory card size: 512 GB | Mounting kit: Yes | Mobile

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

operating systems supported: Android 7.0 | Supported video modes: 1080p | Mobile operating systems supported: iOS 13 | Card reader integrated: Yes | Operating temperature (T-T): 0 - 40 °C | Progressive scan: Yes | Night vision distance: 12 m | Power source type: Power socket | Fixed focal length: 3.83 mm | Built-in microphone: Yes | Screws included: Yes | Width: 82 mm | Total megapixels: 2 MP | Placement supported: Indoor | Number of cameras: 1 | Intelligent Video Surveillance (IVS) system features: Quick movement | Security algorithms: 128-bit AES | AC input frequency: 50-60 Hz | Operating relative humidity (H-H): 10 - 95% | Sensor type: CMOS | Ethernet LAN: Yes | Depth: 82 mm | Lens viewing angle, horizontal: 88.11° | Siren noise level: 90 dB | Lens viewing angle, diagonal: 107.52° | Lens viewing angle, vertical: 46.65° | Compliance certificates: RCM | Compliance certificates: BSMI | Compliance certificates: KC | Compliance certificates: NCC | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: CE | Live view: Yes | Built-in speaker(s): Yes | Motion sensor: Yes | Weatherproof: No | Mounting brackets included: Yes | Night vision: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950