



**Ubiquiti G5
Turret Ultra IP
security camera
Indoor &
outdoor 2688 x
1512 pixels
Ceiling/wall**

Model: UVC-G5-Turret-Ultra

Manufacturer: UBIQUITI

EAN: 810084693575

Product Code: 418916

R2,634

Reset button: Yes | Product colour: White | Cable length: 0.3 m | AC input voltage: 37 - 57 V | Connectivity technology: Wired | Maximum resolution: 2688 x 1512 pixels | Bluetooth: No | Built-in microphone: Yes | Image quality adjustment: Brightness | Image quality adjustment: DNR | Image quality adjustment: Contrast | Built-in HDD: No | Privacy masking: Yes | Ethernet LAN: Yes | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Night vision distance: 30 m | Total megapixels: 4 MP | International Protection (IP) code: IP66 | Diameter: 9 cm | Number of sensors: 1 | Height: 71.2 mm | Processor model: ARM Cortex-A7 | Mounting type: Ceiling/wall | Day/night mode: Yes | Number of lenses: 1 | Number of cameras: 1 | Cables included: LAN (RJ-45) | Image quality adjustment: Colour depth | Housing material: Polycarbonate (PC) | Video formats supported: H.264 | Housing material:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Aluminium | Image quality adjustment: Sharpness | LED type: IR | Weight: 330 g | Power consumption (typical): 4 W | Built-in processor: Yes | Weatherproof: Yes | Noise reduction: Yes | Form factor: Turret | IK code: IK04 | Wi-Fi: No | Protection features: UV resistant | Protection features: Tamper resistant | Operating relative humidity (H-H): 0 - 90% | Ethernet interface type: Fast Ethernet | Frame rate: 30 fps | Noise reduction technology: 2D noise reduction, 3D noise reduction | Operating temperature (T-T): -30 - 50 °C | Ethernet LAN (RJ-45) ports: 1 | Screws included: Yes | Night vision: Yes | Sensor type: CMOS | Placement supported: Indoor & outdoor | Text caption overlay: Yes | Mounting kit: Yes | Infrared (IR) cut-off filter: Yes | Type: IP security camera | Power source type: PoE | Compliance certificates: Federal Communications Commission (FCC) | Lens viewing angle, diagonal: 120.6° | Lens viewing angle, horizontal: 102.4° | Sustainability compliance: Yes | Lens viewing angle, vertical: 54.9° | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Compliance certificates: CE | Warnings: The product contains electronic components do not dispose of with the normal household waste.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950