



Fender AudioBox GO - USB-C Audio Interface

Model: FENDER AUDIOBOX GO

Manufacturer: FENDER

EAN: 673454015021

Product Code: 420112

R2,246

Warnings: Avoid contact with liquids and moisture. | Warnings: Do not open the appliance housing risk of electric shock. | Warnings: Store away from heat and open flame. | 6.35 mm (1/4-inch) output: 2 | XLR combo inputs: 1 | Maximum input level: +10 dBu | Headphone outputs 1/4" (6.35 mm) : 1 | Phantom power supply (± 2 VDC): +48 VDC (± 2 VDC) | Maximum input level: +13 dB | ADC dynamic range (A-wtd, 48 kHz sampling rate): 90 dB | DAC dynamic range (A-wtd, 48 kHz sampling rate): 102 dB | Bit depth: 24 | Gain adjustment range: 50 dB | Gain adjustment range: 50 dB | Type: XLR female, balanced (via combo connector input 1) | Type: 1/4" TS female, unbalanced (input 2) | Type: 1/4" TRS active stereo | Input impedance: 1400 Ω | Headphone frequency: 20 - 20000 Hz | Width: 109.5 mm | Signal-to-Noise Ratio (SNR): 90 dB | Sample rate: 44.1 kHz / 48 kHz / 88.2 kHz / 96 kHz | USB Type-C ports quantity: 1 | Product type: Audio interface | USB Power Delivery (USB PD): Yes | Height: 44 mm | 6.35 mm (1/4-inch) input: 1 | Depth: 85 mm | Weight: 375 g | Microphone frequency: 20 - 20000 Hz | USB version: 2.0 | Product colour: Black

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950