



Large Format Display DAHUA 50 3840 x 2160 pixels 4K Ultra HD Native aspect ratio 16:9 LED Flat DHI-LM50-F400

Model: DHI-LM50-F400

Manufacturer: DAHUA

EAN: 6923169706627

Product Code: 42429

R8,278

- 4K Ultra-HD resolution
- Suitable for continuous 24/7 operation
- 8ms response time for no motion blur, judder or ghosting
- 1.07G colors, for a realistic and immersive visual experience
- High fidelity digital processing for a brilliant and vivid video
- 178°/178° extra-wide viewing angle for overall viewing performance

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- Professional thermal design to extend equipment lifespan

Summary: Dahua Technology LM50-F400. Display diagonal: 127 cm (50"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LED, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 2.0. VESA mounting. Product colour: Black | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Display--Control/Monitors/Light-Series/LM50-F400> | Contrast ratio (typical): 5000:1 | Display brightness (peak): 300 | Display diagonal: 50 | Display number of colours: 1.07 billion colours | Display resolution: 3840 x 2160 | Display technology: LED | HD type: 4K Ultra HD | Maximum refresh rate: 60 | Native aspect ratio: 16:9 | Response time: 8 | Screen shape: Flat | Touchscreen: No | Viewing angle, horizontal: 178 | Viewing angle, vertical: 178 | Built-in speaker(s): Yes | Number of speakers: 2 | RMS rated power: 7 | Market positioning: Business | Product colour: Black | Audio input: Yes | Built-in USB hub: Yes | HDMI: Yes | HDMI ports quantity: 2 | HDMI version: 1.4/2.0 | Headphone out: Yes | USB hub version: 2.0 | VGA (D-Sub) ports quantity: 1 | Panel mounting interface: 200 x 200 | VESA mounting: Yes | AC input frequency: 50 - 60 | AC input voltage: 100 - 240 | Energy consumption (SDR) per 1000 hours: 75 | Energy efficiency class (SDR): G | Energy efficiency scale: A to G | European Product Registry for Energy Labelling (EPREL) code: 750571 | Input current: 2.5 | Power consumption (standby): 0.5 | Power consumption (typical): 110 | Operating relative humidity (H-H): 10 - 80 | Operating temperature (T-T): 0 - 40 | Bezel width (bottom): 22.62 | Bezel width (side): 8.24 | Bezel width (top): 8.24 | Depth (without stand): 87.2 | Height (without stand): 649 | Weight (with stand): 10400 | Width (without stand): 1113.04 | Package depth: 160 | Package height: 800 | Package weight: 13800 | Package width: 1240 | Compliance certificates: CE | Data Sheet (Link): <https://eprel.ec.europa.eu/api/product/750571/fiches?language=EN> | Energy efficiency class: F | EPREL Registration Number: 750571 | EPREL Version Number: 2 | Model: DHI-LM50-F400 | Model name: LM50-F400 | Unit Calculated Volume: 0.1571 | Product Net Weight: 7 | Unit Calculated Weight: 8

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950