



Charger SkyRC NC2500 Pro AA/AAA



Model: SK-100185-01

Manufacturer: SKYRC

EAN: 6930460007568

Product Code: 424404

R2,450

SkyRC NC2500 Pro AA / AAA charger

The SkyRC NC2500 Pro charger allows not only charging AA and AAA batteries, but also regenerating them. The device offers several different modes of operation, and has the added advantage of a run-in function that allows you to run-in model motors that have not been used for a long time. You also have a USB port that supports QC 3.0 fast charging, and the charger is equipped with 6 battery slots.

As many as 4 available features

The NC2500 Pro offers as many as 4 modes of operation. This way you can not only charge the batteries of your choice, but also discharge or regenerate them. In this way you will extend their life! A brake-in function is also available. All this will allow you to optimize the operation of your batteries, take care of their condition, and even protect them from wear and tear or damage!

Charge 6 batteries simultaneously

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

With the NC2500 Pro you can charge up to 6 batteries simultaneously. The device is equipped with 6 slots and offers a maximum current of 2.5A. The charger also offers a special Step Charging mode, which allows you to adjust the amperage for successive charging steps. So you can take even better care of the condition of your batteries and enjoy their optimal performance!

Easy operation

Convenient operation of the device is enabled by a special dial. The charger is also equipped with an easy-to-read display, so you can check the current amperage, voltage and capacity for each channel at any time. On the screen you will also find information about the current operation mode and elapsed time. Just take a look!

Effective protection against overheating

Don't worry that your battery will overheat and be damaged. The charger uses an innovative FlexiPulse algorithm that prevents similar problems! When the device detects that the cell's internal resistance increases above a certain level during charging, it will automatically reduce the amperage to maintain the right temperature. In this way, it will protect the battery from overheating!

Run-in function

The NC2500 Pro is more than just a charger. The device offers an additional run-in function. It allows you to run-in model motors that have not been used for a long time. In this way you will prepare them for the next races and gain confidence that they will not let you down! Bet on proven solutions and achieve better and better results.

Additional USB port - fast charging

With the NC2500 Pro charger you can also charge your phone in a short time. The device is equipped with an additional USB port and supports QC2.0 / QC3.0 fast charging. It also provides voltage and current at 5V / 3A and 9V / 2A. This makes the charger perfect for a variety of scenarios. You no longer have to wait too long for your smartphone to be ready for use!

In the box

- BD350 battery discharger / tester
- XT60 connection cable

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Brand	SkyRC
Model	NC2500 Pro
Input	DC 12V / 3A
Battery type	NiMH / NiCD
Battery size	AA / AAA
Charging intensity	0.1-2.5A
Discharge current	0.1-1.5A
Discharge cutoff voltage	0.8-1.0V (adjustable)
USB output	QC3.0 5V / 3A, 9V / 2A, 18W max $\pm 5\%$ - ΔV : 1-8mV (adjustable)
Current (trickle)	30-99mA / OFF
Temperature protection	55-65°C (adjustable)
Operating temperature	From 0°C to 40°C
Ambient humidity during operation	0-75%
Storage temperature	From -10°C to 70°C
Ambient humidity during storage	0-75%
Display	LCD
Dimensions	148 x 135 x 65mm
Weight	600g

Last delivery: 10.09.2026, Net weight: 600, Box width: 17,00, Box height: 9,50, Box length: 25,00, Gross weight: 990, Input voltage AC (V): DC 12, Charging current (A): 0,1 - 2,5, GPSR Link: https://psr-assets.innpro.pl/rc_models/sg_rc_models_charging.pdf, PPWR: <https://ppwr.innpro.pl/skyrc>

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950