



**LCD Monitor
VIEWSONIC
TD2430 24
Touch
Touchscreen
Panel MVA
1920x1080 16:9
25 ms Speakers
TD2430**

Model: TD2430

Manufacturer: VIEWSONIC

EAN: 00766907846911

Product Code: 42531

R6,952

- 10-point Projected Capacitive Touch
- SuperClear® MVA-type panel technology
- Frameless Design
- Versatile Connectivity
- Durable, Scratch-resistant Screen

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Laid flat or angled for customized comfort, this display delivers touchscreen versatility to the max. Offering fantastic flexibility for retail, education, or business settings, the ViewSonic® TD2430 is a 24" (23.6" viewable) Full HD display with 10-point multi-touch functionality. Delivering adjustable positioning, wide-angle viewing, and a durable design, the TD2430 has everything to accommodate your unique needs. Adding even more convenience, cross-compatibility with a wide range of operating systems includes Windows 10, and certain Android and Linux versions.* With a sleek edge-to-edge screen and frameless bezel, this intuitive touchscreen performs like your favorite tablet or smartphone to deliver a highly accurate, ultra-responsive touch experience ideal for interactivity in public environments, kiosk and wayfinding applications, classroom settings, and more.

*Supports Windows 7/8/10, Linux 2.6.38 or later, and Android 4.0 or later.

Summary: Viewsonic TD2430. Display diagonal: 59.9 cm (23.6"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting. Product colour: Black | Vendor Homepage: <https://www.viewsonic.com/la/td2430.html> | Contrast ratio (dynamic): 50000000:1 | Contrast ratio (typical): 3000:1 | Display brightness: 200 | Display diagonal: 23.6 | Display diagonal (metric): 60 | Display resolution: 1920 x 1080 | Display technology: LCD | HD type: Full HD | Horizontal scan range: 24 - 82 | Maximum refresh rate: 76 | Native aspect ratio: 16:9 | Number of simultaneous touchpoints: 10 | Panel type: VA | Pixel pitch: 0.2715 x 0.2715 | Response time: 5 | Screen shape: Flat | Touch technology: Multi-touch | Touchscreen: Yes | Touchscreen technology: Projected capacitive system | Touchscreen type: Multi-user | Vertical scan range: 50 - 75 | Viewing angle, horizontal: 178 | Viewing angle, vertical: 178 | AMD FreeSync: No | Linux operating systems supported: Yes | Mac operating systems supported: Yes | NVIDIA G-SYNC: No | Other operating systems supported: Android | Windows operating systems supported: Windows 10/Windows 7/Windows 8 | Built-in camera: No | Built-in microphone: No | Built-in speaker(s): Yes | Number of speakers: 2 | RMS rated power: 5 | Product colour: Black | Built-in USB hub: Yes | DisplayPort version: 1.2 | DisplayPorts quantity: 1 | HDMI: Yes | HDMI ports quantity: 1 | HDMI version: 1.4 | Headphone out: Yes | Headphone outputs: 1 | Number of upstream ports: 1 | Number of USB Type-B upstream ports quantity: 1 | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | USB Type-A downstream ports quantity: 2 | USB upstream port type: USB Type-B | VGA (D-Sub) ports quantity: 1 | Panel mounting interface: 100 x 100 | Tilt adjustment: Yes | Tilt angle range: 20 - 53 | VESA mounting: Yes | Wall mountable: Yes | AC input frequency: 50 - 60 | AC input voltage: 100-240 | Energy consumption (SDR) per 1000 hours: 15 | Energy efficiency

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

class (SDR): E | European Product Registry for Energy Labelling (EPREL) code: 404623 | Power consumption (typical): 25 | Power supply type: AC | Operating relative humidity (H-H): 20 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -20 - 60 | Depth (with stand): 47 | Height (with stand): 353 | Weight (with stand): 5510 | Width (with stand): 573 | Package depth: 140 | Package height: 435 | Package weight: 7100 | Package width: 643 | Cables included: AC/Audio (3.5mm)/HDMI/USB | Sustainability certificates: ENERGY STAR/ErP | Certification: cTUVus, FCC-B, ICES003, Energy Star 8.0, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, RCM, GEMS, CCC, China RoHS, China Energy Label, CECP | Compliance certificates: CE/REACH/RoHS | Display viewable area (HxV): 521.28 x 293.22 | Mobile operating systems supported: Android | Weight: 5500 | Harmonized System (HS) code: 8528521000 | Pallet gross height: 1890 | Pallet gross length: 1000 | Pallet gross width: 1200 | Products per master (outer) case: 1 | Data Sheet (Link): <https://eprel.ec.europa.eu/api/product/404623/fiches?language=EN> | Energy efficiency class: E | EPREL Registration Number: 404623 | EPREL Version Number: 2 | Model name: TD2430 | Unit Calculated Volume: 0.03853 | Product Net Weight: 5.5 | Unit Calculated Weight: 7.45

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950