



InLine Mini DisplayPort HDMI Adaptor Aluminum with Audio, 4K/60Hz, black, 0.15m

Model: 17193S

Manufacturer: INLINE

EAN: 4043718290482

Product Code: 456849

R1,345

Active signal conversion for reliable image quality:The integrated Parade PS176 chipset enables stable transmission from Mini DisplayPort to HDMI – even at high resolutions.

4K at 60Hz for professional applications:Transmits image and sound signals in Ultra HD resolution – ideal for high-quality presentations and modern workplaces.

High-quality construction for continuous use:With solid copper wires, triple shielding and gold-plated contacts for a long-lasting and interference-free connection.

Maximum compatibility with DisplayPort 1.2a and HDMI 2.0:Ideal for use with current IT systems and AV infrastructures in offices, conference rooms or training facilities.

Easy to integrate without driver installation:Plug & Play solution for quick setup – saves time during system changes or temporary installations.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The InLine® Mini DisplayPort to HDMI converter cable is a reliable solution for actively converting digital video and audio signals. It transmits content in 4K resolution at 60Hz, making it ideal for professional applications such as conference rooms, training environments or demanding workplace concepts. The built-in Parade PS176 chipset actively converts the signal, enabling stable image and sound transmission even in high-resolution applications. The robust design with solid copper wires, triple shielding and gold-plated contacts provides reliable protection against interference and ensures a long service life. Compatibility with DisplayPort 1.2a and HDMI 2.0 allows use with numerous modern devices. The plug & play function makes integration particularly easy – without the need for additional driver installation.

DisplayPort 1.2a and High Speed HDMI 2.0 compatible

Signal direction: Computer Mini DisplayPort output to HDMI monitor input

Solid copper wires

Triple-shielded cable

Gold-plated contacts

For the transmission of video and audio signals

Data transfer rate up to 18 Gb/s

Resolution up to 3840 × 2160 at 60 Hz with RGB or YCbCr4:4:4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950