



InLine USB Power Adapter Single, 100- 240V to 5V/1.2A white



Model: 31504W

Manufacturer: INLINE

EAN: 4043718289424

Product Code: 465857

R889

Stable power supply via the power outlet: Reliably converts 100-240V AC to 5V DC for safe charging of mobile USB devices.

Compact 1-port solution: The single USB-A socket provides a clearly defined output of up to 1.2A, ideal for continuous operation.

High operational reliability: Protection functions against overheating, overvoltage, overcurrent, and short circuits support trouble-free use.

Efficiency-oriented design: The idle power consumption of only 0.09W enables economical operation.

Universally applicable: The wide input voltage range of 100-240V AC facilitates use in a wide variety of environments.

The InLine® USB Charger Single provides a reliable power supply via any standard power outlet. The

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

wide input range of 100-240V AC makes the device flexible in use. The input voltage is converted into a stable output voltage of 5V DC. The USB-A socket delivers up to 1.2A, making it particularly suitable for devices that do not require high charging currents. These include mobile data readers, e-readers, and smaller communication devices.

The compact design facilitates use in environments where several power supplies are operated in parallel. The low power consumption of 0.09W when idle supports energy-efficient operation. Several integrated protection functions, such as overheating, overvoltage, overcurrent, and short-circuit protection, contribute to reliable operation and improve the operational safety of the connected device. The charger is therefore particularly suitable for applications where a constant and reliable power supply for USB devices is required.

Output power: 6.0W

Average efficiency: 76.66%

Input current: 0.5A

Output connections: 1x USB-A