



InLine 32335W network transceiver module Copper 10000 Mbit/s SFP+

Model: 32335W

Manufacturer: INLINE

EAN: 4043718345151

Product Code: 465968

R3,235

RJ-45 copper connector for 10GBASE-T: Connects classic Ethernet components directly via Cat.6a cables – without fibre optics.

Up to 30 m range: Ideal for short connections in server racks, patch panels or equipment rooms.

Supports auto-negotiation: For 10G/5G/2.5G/1G – automatic adjustment to available bandwidth.

Cost-effective alternative to fibre optics: Saves on expensive fibre optic components, ideal for copper-based infrastructures.

Hot-plug capable and MSA-compatible: Easy to retrofit in many switches and routers with SFP+ slot.

The InLine® SFP+ Module 32335W expands your network with a powerful copper solution for

10GBASE-T applications. With a range of up to 30 metres on Cat.6a cables, the module is ideal for

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

use in data centres, server cabinets or for connecting high-speed devices in close proximity. Thanks to the standardised RJ-45 interface, servers, NAS systems or switches can be easily connected via existing twisted pair cables – without additional converters or fibre optic technology. The module supports auto-negotiation for 10G, 5G, 2.5G and 1G, so the connection automatically adapts to the connected device and the available bandwidth. With a power consumption of up to 3 W, the module is slightly warmer than fibre optic transceivers, but allows for easy retrofitting on a limited budget or with infrastructure restrictions. The hot-plug function and MSA compatibility ensure easy integration into existing systems – without interrupting operation.

Form factor: SFP+ module (copper)

Standard: 10GBASE-T, 5GBASE-T, 2.5GBASE-T, 1000BASE-T

Connector: RJ-45 (8P8C)

Range: up to 30 m (at 10G over Cat.6a)

Compatibility: Auto-negotiation for 10G/5G/2.5G/1G

Hot-plug capable: Yes

Voltage: 3.3 V (3.13–3.47 V)

Current consumption: approx. 900 mA

Power consumption: max. 3.0 W

Operating temperature: 0 °C to +65 °C

DDM monitoring: not supported

MSA SFP+ compliant

Note on coding:

Our SFP modules are factory-coded – whether for Cisco, Intel or other systems, which may limit your choice.

For maximum compatibility, we now programme individually according to customer requirements.

Please contact your sales representative.