



InLine 33380V network card Ethernet 1000 Mbit/s



Model: 33380V

Manufacturer: INLINE

EAN: 4043718345441

Product Code: 466152

R2,783

Four independent Gigabit LAN ports via USB: Ideal for virtualisation, network segmentation or redundant connections – each port can be used independently.

Optimised for professional applications: Supports VLAN tagging, QoS, time synchronisation (IEEE1588) and jumbo frames – ideal for demanding IT infrastructures.

High compatibility & flexibility: Compatible with Windows, Linux and macOS – enables use in a wide range of industrial and server environments.

Plug & Play with intelligent USB technology: The integrated VL820 chip enables reliable data transfer at up to 5 Gb/s via USB 3.2 Gen.1.

Compact form factor & robust design: Fits into any IT environment – ideal for embedded systems, server cabinets or mobile diagnostic tools.

The InLine® USB-A 3.2 Gen.1 to 4x RJ45 Gigabit Ethernet Adapter expands professional IT systems with four full-featured, independent LAN interfaces. Whether for virtualisation, multi-NIC

configurations, network segmentation or diagnostic systems, this adapter offers reliable Gigabit

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Ethernet connectivity in a compact form. Thanks to the USB 3.2 Gen.1 interface with up to 5 Gb/s transfer rate, the four ports can be connected to the host system via a single USB cable – without additional power supply or driver installation under common operating systems.

The integrated Realtek and VIA chipsets guarantee stable, high-performance data transmission and offer professional features such as VLAN tagging (IEEE802.1Q), Quality of Service (IEEE802.1P), precise time synchronisation (IEEE1588v1/v2), flow control and jumbo frame support up to 9 KB. Automatic crossover detection and extensive offload functions ensure additional performance and system relief.

Ideal for servers, industrial PCs, embedded systems or mobile use in maintenance and network diagnostics, this adapter is the perfect tool for IT professionals who depend on flexible, reliable network solutions.

USB compatibility: backward compatible with USB 2.0 / 1.1

Energy efficiency: IEEE802.3az

Flow control: IEEE802.3x

Operating systems: Windows XP – 11, Windows Server 2008 R2 – 2022, macOS 10.6–10.13, Linux 2.6.x – 4.x

Checksum & offload: NDIS5/6, Large Send Offload v1/v2

LED indicators per port: Connection and activity status

Power consumption: max. 5 W

Operating temperature: 0 °C to +70 °C

Storage temperature: -55 °C to +125 °C

Dimensions: approx. 73 × 70 × 25 mm