



## InLine USB 3.0 10 Port Hub Aluminium Case with 4A Power Supply, black



Model: 35395C

Manufacturer: INLINE

EAN: 4043718214419

Product Code: 466427

# R2,578

**High data transfer rate:** Achieve speeds of up to 5 Gb/s - ideal for demanding applications and fast file transfers.

**Simultaneous operation:** The included 4 A power supply allows you to operate multiple devices at the same time without any loss of performance.

**Robust aluminum design:** The elegant, black aluminum housing combines sophisticated design with outstanding stability.

**Comprehensive compatibility:** Thanks to backwards compatibility (USB 3.1, 3.0, 2.0, 1.1), you have flexible access to a wide range of systems.

Benefit from an active USB hub that has been specially developed for professional applications. With the InLine® USB 3.2 Gen.1 hub, you get a solution that meets the highest demands - whether in the data center or in the office. The ultra-fast data transfer of up to 5 Gb/s and the reliable power supply

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

via the high-performance power supply unit enable trouble-free operation, even if several devices are connected at the same time. The high-quality aluminum housing in elegant black is not only visually appealing, but also offers increased stability and durability. The simple operation via an ON/OFF button and the LED status indicators mean you always have an overview of the connection status.

Material: Aluminum

Color: Black

Output interface: 10x USB-A 3.2 Gen.1 sockets

System: Windows XP and MAC OS X or higher

Product dimensions: 188 (L) x 40 (W) x 40 (H) mm

Weight: 305 g

Operating temperature: 5 ° C ~ 40 ° C

Storage temperature: -20 ° C to 70 ° C

### **Content of delivery:**

1x USB 3.2 Gen.1 hub

1x USB 3.2 Gen.1 data cable (1 m)

1x operating instructions (German/English)

1x power supply unit (1.2 m) 12 V/4 A

### **Technical data power supply unit:**

Input voltage: 100-240 V

Input alternating current frequency: ~50/60 Hz, 1.5 A

Output voltage: 12.0 V DC

Output current: max. 4.0 A

Output power: 48.0 W

Average efficiency during operation: 88.62 %

Efficiency at low load (10 %): 86.66 %

Power consumption at no load: 0.083 W

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950