



InLine 51124I interface cards/adapter Internal



Model: 51124I

Manufacturer: INLINE

EAN: 4043718341214

Product Code: 469092

R3,527

Robust M12 interfacefor industrial and professional network applications

High data rates10/100/1000 Mb/s & 2.5 Gb/s (auto-negotiation)

PoE/PoE+(up to 25.5 W) to power compatible devices

VLAN tagging, PXE bootand Wake-on-LAN support

Standard and low-profile slot bracketsfor maximum compatibility;for maximum compatibility

The InLine® Gigabit network card was specially developed for robust and reliable network connections in industrial environments. Thanks to the M12 x-coded connection, it offers a secure and resilient connection that is ideal for use in machines, control systems and monitoring solutions. With a data rate of up to 2.5 Gb/s via the PCIe 2.1 x1 interface, it ensures fast and stable transmission of large amounts of data. Thanks to the integrated PoE+ support (IEEE 802.3af/802.3at), connected devices such as surveillance cameras, sensors or access points can be supplied with power directly via the network cable; a separate power source is not required. Additional functions such as Jumbo Frames (up to 16 KB) for more efficient data transmission, VLAN tagging for network segmentation,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Wake-on-LAN for remote system startup and remote access to the network; for remote booting of systems and PXE support for network-based boot processes make the card a versatile solution for demanding network environments.

Technical data:

External: 1x M12 socket, 8-pin, x-coded

Internal: 1x PCI Express x1 (2.1), 1 x SATA 15-pin power connector

Bus type: PCIe v2.1, x1 lane (operational in x1, x4, x8, x16 slots)

Chip set: Realtek RTL8125B

Supported protocols: IPv4, IPv6

LED: Indicator for action (green) and connection (orange)

Supported IEEE standards:

IEEE 802.3 (Ethernet), IEEE 802.3u (Fast Ethernet), IEEE 802.3ab (Gigabit Ethernet)

IEEE 802.3x (Flow Control), IEEE 802.1Q (VLAN)

IEEE 802.3af (PoE) / 802.3at (PoE+)

IEEE 802.1P Layer 2 Priority Encoding - Prioritize network: Efficiently control QoS

Advanced functions:

Supports PXE (Preboot Execution Environment)

Supports RealWoW (Remote Wake-on-LAN over the Internet)

Supports crossover detection and automatic correction

Supports Microsoft NDIS5/NDIS6 Checksum Offload (IPv4, IPv6, TCP, UDP)

Jumbo Frames: Up to 16 KB

Environmental conditions:

Operating temperature: 0 °C to 55 °C

Storage temperature: -40 °C to 70 °C

Maximum humidity: 90%

Supported operating systems:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Windows: 11, 10, 8.1, 8, 7 (32/64 bit)

Linux: Native support for Fedora, SUSE, Ubuntu, Red Hat

DOS and Novell

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950