

InLine 66659M network card Fiber 1000 Mbit/s

Model: 66659M

Manufacturer: INLINE

EAN: 4043718345434

Product Code: 471120

R2,448

Modular fibre optic connection via USB-C: Flexible use thanks to SFP port for various transceivers – ideal for changing network architectures.
Gigabit performance with energy efficiency: Supports up to 1,000 Mb/s and reduces power consumption thanks to IEEE802.3az.
Compatible with many operating systems: Broad support for Windows, macOS and Linux enables versatile integrations.
Loss-free data transmission: On-chip buffer, flow control and checksum offload ensure reliable and fast communication.
Ideal for industrial and IT environments: Works without interference in electromagnetically sensitive areas and over long distances.

The InLine® USB-C to SFP Gigabit Fiber Network Adapter is the ideal solution for professional network environments that require flexibility, reliability and compatibility. With its modular SFP port, various fiber optic transceivers (e.g. SX, LX) can be used – perfect for different ranges and

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

infrastructures. The adapter supports network speeds of up to 1,000 Mb/s via the USB-C port, making it ideal for fast, stable connections with low latency.
The adapter scores particularly well in industrial applications, data centres or IT integration with features such as IEEE802.3az for energy saving, flow control to prevent packet loss and QoS capability for prioritised data transmission. Integrated support for VLAN tagging and automatic cable type detection also ensures easy integration into existing systems.
Thanks to its broad operating system support for Windows, macOS and Linux, the device is extremely versatile – for example, for temporary network connections, notebooks in service management or for permanent integration into rack solutions. The integrated on-chip buffer and extensive offload functions relieve the system and ensure loss-free data transmission, even under high loads.

Network protocols: IEEE802.3 / 802.3u / 802.3ab
VLAN / prioritisation: IEEE802.1Q, Layer 2 Priority
Jumbo frames: Up to 9K
Power saving functions: Power Down / Link Down / LPM
Skew/polarity correction
Crossover detection (Auto-MDI/MDI-X)
Chipset: Realtek RTL8153

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950