



**InLine
Installation
cable Cat.7a,
S/FTP (PiMF)
4x2x0.58
AWG23
1200MHz B2ca
300m**

Model: 71300I

Manufacturer: INLINE

EAN: 4043718312634

Product Code: 471894

R10,463

The installation cable is delivered in a drum box for easy removal of the required length. The packaging consists of a plastic reel on which the data cable is rolled up. This roll is fixed in a reinforced cardboard box, which ensures simple and tangle-free unrolling. The reel box offers the following advantages:

Cost reduction through easy handling on the construction site without additional unwinding device

Handy and stackable packaging, convenient to transport in the construction site vehicle

Low weight (can also be sent by parcel service)

Avoidance of soiling and transport damage to the cable through repackaging by means of cardboard

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Reduction of cutting costs for small quantities

Technical data:

Cable for **installation**

Cat. 7a installation cable up to 1200MHz

Construction: 4x2xAWG23/1 PIMF (0.58mm²)

Suitable up to 10 Gbit

Full copper cores

Impedance: 100Ohm, DC resistance: max. 93.8 Ohm/km

Sheath halogen-free LSZH

Sheath colour orange

Construction: In pairs in metal foil

Overall braided shielding

Cable diameter approx. 7.8mm

Installation temperature: 0 - 50°C, Operating temperature: -20°C - 60°C, Storage temperature: -20°C - 50°C

With remaining metre indication on cable

Fire behaviour B2ca according to EN 50575: 2014 / A1:2016

Note: The drum box is only available for the bundles 50m, 100m, 300m, whereas 500m is delivered on a drum, the lengths 10m and 25m are delivered in a box.