



**ASUS ProArt
PA279CV
computer
monitor 68.6 cm
(27) 3840 x
2160 pixels 4K
Ultra HD LED
Black, Silver**

Model: PA279CV

Manufacturer: ASUS

EAN: 4718017853200

Product Code: 47296

R7,920

Certification: TUV Flicker-free , TUV Low Blue Light, Calman Verified | Display diagonal: 68.6 cm (27")
| Display brightness (typical): 350 cd/m² | Tilt angle range: -5 - 35° | Aspect ratio: 16:9 | Display
resolution: 3840 x 2160 pixels | Power consumption (off): 0.2 W | Product colour: Black | Low Blue
Light technology: Yes | Energy efficiency class (HDR): G | AC (power) in: Yes | Viewable size diagonal:
68.5 cm | Energy efficiency class (SDR): F | HDMI: Yes | Dynamic contrast ratio marketing name:
SmartContrast | USB Type-A downstream ports quantity: 4 | Width (without stand): 614 mm |
Harmonized System (HS) code: 85285210 | Energy consumption (SDR) per 1000 hours: 26 kWh |

sRGB coverage (typical): 100% | Depth (without stand): 60 mm | High Dynamic Range (HDR)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

technology: High Dynamic Range 10 (HDR10) | Feet colour: Silver | Headphone out: Yes | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | High Dynamic Range (HDR) supported: Yes | Number of upstream ports: 4 | Weight (without stand): 5.7 kg | Flicker-free technology: Yes | USB Type-C downstream ports quantity: 1 | Stand included: Yes | Height (without stand): 370 mm | Frameless design: Yes | Energy efficiency scale: A to G | Maximum refresh rate: 60 Hz | VESA Adaptive Sync support: Yes | Energy consumption (HDR) per 1000 hours: 57 kWh | Front bezel colour: Black | Detachable stand: Yes | Weight (with stand): 8.6 kg | Commodity Classification Automated Tracking System (CCATS): 8528521000 | Adjustable height (max): 15 cm | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Warnings: Unplug the monitor from the power source before cleaning. | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | European Product Registry for Energy Labelling (EPREL) code: 403921 | Package weight: 11.2 kg | Number of speakers: 2 | Height adjustment: Yes | Package depth: 161 mm | Supported graphics resolutions: 3840 x 2160 | Headphone connectivity: 3.5 mm | Quick start guide: Yes | Depth (with stand): 227.8 mm | Width (with stand): 614 mm | HDMI ports quantity: 2 | HD type: 4K Ultra HD | Response time: 5 ms | Pivot angle: -90 - 90° | DisplayPort version: 1.2 | Screen shape: Flat | Swivel angle range: -45 - 45° | Height (with stand): 523.4 mm | Swivelling: Yes | Viewable size, vertical: 33.6 cm | Viewing angle, horizontal: 178° | Digital vertical frequency: 40 - 60 Hz | Built-in USB hub: Yes | Display number of colours: 1.073 billion colours | Cable lock slot type: Kensington | DisplayPorts quantity: 1 | Native aspect ratio: 16:9 | Built-in camera: No | HDCP: Yes | Digital horizontal frequency: 29 - 160 kHz | Tilt adjustment: Yes | Display technology: LED | Contrast ratio (dynamic): 100000000:1 | Cables included: AC | Cable lock slot: Yes | Power consumption (typical): 32.1 W | Viewing angle, vertical: 178° | Touchscreen: No | Package type: Box | Audio input: No | Package height: 680 mm | Contrast ratio (typical): 1000:1 | RMS rated power: 2 W | Pixel pitch: 0.155 x 0.155 mm | Market positioning: Photo editing | Viewable size, horizontal: 59.7 cm | Panel mounting interface: 100 x 100 mm | AC input frequency: 50 - 60 Hz | DVI port: No | Pivot: Yes | HDMI version: 2.0 | Power consumption (standby): 0.5 W | VESA mounting: Yes | Headphone outputs: 1 | Built-in speaker(s): Yes | Package width: 516 mm | Panel type: IPS | AC input voltage: 100 - 240 V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950