



ASUS ProArt PA278QV computer monitor 68.6 cm (27) 2560 x 1440 pixels Quad HD LED Black

Model: PA278QV

Manufacturer: ASUS

EAN: 4718017603614

Product Code: 47297

R4,770

Certification: Energy Star, BSMI, CB, CCC, CEL level , CU, ErP, FCC, ISO-9241-307, J-MOSS, KCC, PSE, TUV-Ergo, TUV-GS, UkrSEPRO, UL/cUL, VCCI, WEEE, WHQL (Windows 10, Windows 7), RCM, TUV Flicker-free , KC , eStandby, TUV Low Blue Light, TCO, ICES-3, PC recycle | Colour gamut standard: sRGB | European Product Registry for Energy Labelling (EPREL) code: 384209 | Warnings: Unplug the monitor from the power source before cleaning. | Adjustable height (max): 15 cm | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Supported graphics resolutions: 1280 x 800

(WXGA) | Width (with stand): 615 mm | Supported graphics resolutions: 1920 x 1080 (HD 1080) |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Supported graphics resolutions: 800 x 600 (SVGA) | Display surface: Matt | Height (with stand): 532 mm | Supported graphics resolutions: 1280 x 960 | DisplayPort version: 1.2 | Display resolution: 2560 x 1440 pixels | Cable lock slot: Yes | Viewing angle, vertical: 178° | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1920 x 1200 (WUXGA) | Supported graphics resolutions: 1280 x 768 (WXGA) | Native aspect ratio: 16:9 | LED indicators: Yes | Contrast ratio (dynamic): 100000000:1 | Supported graphics resolutions: 1280 x 1024 (SXGA) | Supported graphics resolutions: 720 x 576 | Storage temperature (T-T): -20 - 60 °C | Supported graphics resolutions: 1152 x 864 (XGA+) | Screen shape: Flat | Operating temperature (T-T): 0 - 40 °C | Supported graphics resolutions: 720 x 400 | Supported graphics resolutions: 1680 x 1050 (WSXGA+) | Depth (with stand): 226 mm | Supported graphics resolutions: 1280 x 720 (HD 720) | Display brightness (typical): 350 cd/m² | Supported graphics resolutions: 1024 x 768 (XGA) | Supported graphics resolutions: 1440 x 900 (WXGA+) | Supported graphics resolutions: 720 x 480 | Product colour: Black | Power consumption (off): 0.3 W | Tilt angle range: -5 - 35° | HDCP: Yes | Response time: 5 ms | HD type: Quad HD | Viewing angle, horizontal: 178° | Display diagonal: 68.6 cm (27") | DisplayPorts quantity: 1 | AC input voltage: 100 - 240 V | NVIDIA G-SYNC: No | Package weight: 10.8 kg | HDMI version: 1.4 | Supported video modes: 720p | Pivot: Yes | Package depth: 216 mm | VESA Adaptive Sync support: Yes | Mini DisplayPorts quantity: 1 | Maximum refresh rate: 75 Hz | On Screen Display (OSD): Yes | Energy efficiency scale: A to G | Supported video modes: 480p | Supported video modes: 1080p | DVI port: Yes | Viewable size, horizontal: 59.7 cm | AMD FreeSync: No | Feet colour: Black | Headphone outputs: 1 | Built-in speaker(s): Yes | Height adjustment: Yes | Market positioning: Graphics design | Tilt adjustment: Yes | Number of upstream ports: 1 | Flicker-free technology: Yes | Supported video modes: 576p | Package height: 464 mm | Pivot angle: -90 - 90° | Touchscreen: No | Panel type: IPS | VESA mounting: Yes | Digital vertical frequency: 46 - 75 Hz | Swivel angle range: -90 - 90° | Stand included: Yes | DVI-D ports quantity: 1 | Number of speakers: 2 | Number of OSD languages: 21 | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | Width (without stand): 615 mm | Swivelling: Yes | Viewable size, vertical: 33.6 cm | Audio input: Yes | Dynamic contrast ratio marketing name: SmartContrast | Package width: 735 mm | Power consumption (standby): 0.5 W | Depth (without stand): 51 mm | Headphone out: Yes | Viewable size diagonal: 68.5 cm | Cable lock slot type: Kensington | Display technology: LED | Weight (with stand): 7.72 kg | Built-in USB hub: Yes | Power consumption (typical): 32.1 W | Weight (without stand): 4.96 kg | Built-in camera: No | HDMI: Yes | Cables included: AC | sRGB coverage (typical): 100% | Pixel pitch: 0.2331 x 0.2331 mm | Energy consumption (SDR) per 1000 hours: 22 kWh | Frameless design: Yes | Panel mounting interface: 100 x 100 mm | Headphone connectivity: 3.5 mm | Low Blue Light technology: Yes | On Screen Display (OSD) languages: Turkish | On Screen Display (OSD) languages: Simplified Chinese | Digital

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

horizontal frequency: 30 - 112 kHz | On Screen Display (OSD) languages: Hungarian | On Screen Display (OSD) languages: Japanese | On Screen Display (OSD) languages: Spanish | On Screen Display (OSD) languages: Croatian | On Screen Display (OSD) languages: German | On Screen Display (OSD) languages: Italian | On Screen Display (OSD) languages: Dutch | Contrast ratio (typical): 1000:1 | On Screen Display (OSD) languages: Polish | On Screen Display (OSD) languages: Indonesian | USB Type-A downstream ports quantity: 4 | Harmonized System (HS) code: 85285210 | Energy efficiency class (SDR): E | On Screen Display (OSD) languages: Russian | On Screen Display (OSD) languages: Czech | RMS rated power: 4 W | On Screen Display (OSD) languages: Traditional Chinese | On Screen Display (OSD) languages: French | On Screen Display (OSD) languages: Korean | On Screen Display (OSD) languages: Romanian | Height (without stand): 372 mm | On Screen Display (OSD) languages: Portuguese | Display number of colours: 16.78 million colours | On Screen Display (OSD) languages: English | HDMI ports quantity: 1 | On Screen Display (OSD) languages: Thai

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950