



ASUS ProArt PA248CRV computer monitor 61.2 cm (24.1) 1920 x 1200 pixels WUXGA LCD Black, Silver



Model: PA248CRV

Manufacturer: ASUS

EAN: 4711081951490

Product Code: 47307

R5,850

Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Warnings: Unplug the monitor from the power source before cleaning. | European Product Registry for Energy Labelling (EPREL) code: 1412838 | Colour gamut standard: DCI-P3 | Height adjustment: Yes | Panel mounting interface: 100 x 100 mm | HDMI version: 1.4 | Display technology: LCD | Power consumption (typical): 12.35 W | Digital vertical frequency: 48 - 75 Hz | Height adjustment: 13 cm | Market positioning: Graphics design | Backlight type: LED | VESA mounting: Yes | Viewable size, horizontal: 51.8 cm | Maximum refresh rate: 75 Hz | Pivot: Yes | Headphone outputs: 1 | Built-in speaker(s): Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Built-in USB hub: Yes | Feet colour: Silver | AC input frequency: 50 - 60 Hz | Display resolution: 1920 x 1200 pixels | Native aspect ratio: 16:10 | High Dynamic Range (HDR) supported: Yes | Energy efficiency scale: A to G | Package depth: 126 mm | VESA Adaptive Sync support: Yes | Low Blue Light technology: Yes | Anti-glare screen: Yes | HD type: WUXGA | Headphone out: Yes | Response time: 5 ms | Swivel angle range: -30 - 30° | DisplayPorts quantity: 2 | Width (without stand): 531.7 mm | Package height: 414 mm | Depth (with stand): 190.4 mm | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | HDCP version: 1.4 | Pixel density: 94 ppi | Energy consumption (HDR) per 1000 hours: 30 kWh | Energy consumption (SDR) per 1000 hours: 15 kWh | Height (without stand): 350.2 mm | Swivelling: Yes | Pivot angle: -90 - 90° | Depth (without stand): 44.1 mm | sRGB coverage (typical): 100% | High Dynamic Range (HDR) technology: High Dynamic Range 10 (HDR10) | Touchscreen: No | HDCP: Yes | Built-in camera: No | Weight (without stand): 4.2 kg | Tilt adjustment: Yes | Package type: Box | Viewing angle, horizontal: 178° | USB Type-C DisplayPort Alternate Mode: Yes | Energy efficiency class (HDR): G | Package width: 610 mm | Screen shape: Flat | AC input voltage: 100 - 240 V | Width (with stand): 531.7 mm | Weight (with stand): 5.9 kg | Viewable size, vertical: 32.4 cm | HDMI: Yes | Panel type: IPS | Wall mountable: Yes | Charging port type: USB Type-C | Flicker-free technology: Yes | USB Type-C downstream ports quantity: 1 | DisplayPort version: 1.4 | Height (with stand): 529.2 mm | USB Power Delivery up to: 96 W | Cable lock slot: Yes | Digital horizontal frequency: 95 - 95 kHz | USB Power Delivery (USB PD): Yes | Number of speakers: 2 | Cable lock slot type: Kensington | USB Type-A downstream ports quantity: 3 | Package weight: 8.5 kg | USB upstream port type: USB Type-C | Contrast ratio (typical): 1000:1 | RMS rated power: 4 W | HDMI ports quantity: 2 | Power consumption (PowerSave): 0.5 W | Pixel pitch: 0.27 x 0.27 mm | Colour gamut: 97% | Viewing angle, vertical: 178° | Energy efficiency class (SDR): D | Display number of colours: 16.7 million colours | Product colour: Black | Display diagonal: 61.2 cm (24.1") | Tilt angle range: -5 - 23° | Display brightness (typical): 350 cd/m²

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950