



DELL P Series P2725H 68.6 cm (27) 1920 x 1080 px Full HD LCD computer monitor, black

Model: 210-BMGC

Manufacturer: DELL

EAN: 5397184821749

Product Code: 47324

R3,741

Display resolution: 1920 x 1080 pixels | AC input frequency: 50/60 Hz | Panel mounting interface: 100 x 100 mm | Width (with stand): 610.7 mm | Cable lock slot type: Kensington | Bezel width (side): 6.4 mm | Anti-glare screen: Yes | Operating relative humidity (H-H): 10 - 80% | Cable lock slot: Yes | Pivot angle: -90 - 90° | Power supply type: Internal | Cable management: Yes | Storage relative humidity (H-H): 5 - 90% | Screen shape: Flat | Vertical scan range: 48 - 76 Hz | LED backlight: Yes | AMD FreeSync: No | Height (without stand): 354.7 mm | Non-operating altitude: 0 - 12192 m | NVIDIA G-SYNC: No | Mac operating systems supported: MacOS | Backlight type: LED | Height adjustment: 15 cm | Low Blue Light technology: Yes | Weight (with stand): 5.7 kg | Display number of colours: 16.7 million colours | Touchscreen: No | sRGB coverage (typical): 99% | DisplayPort cable length: 1.8 m | Pixel pitch: 0.3114 x 0.3114 mm | HDCP version: 1.4 | VGA (D-Sub) ports quantity: 1 | Surface hardness: 3H | Operating temperature (T-T): 0 - 40 °C | Built-in speaker(s): No | Headphone out: No |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

LED indicators: Yes | Power consumption (typical): 15.8 W | Depth (with stand): 192.3 mm | Operating altitude: 0 - 5000 m | Display diagonal: 68.6 cm (27") | USB Power Delivery up to: 15 W | Energy efficiency class (HDR): Not available | Height adjustment: Yes | Power consumption (off): 0.3 W | On Screen Display (OSD): Yes | Energy efficiency scale: A to G | Dell ComfortView technology: Yes | Viewing angle, horizontal: 178° | Maximum refresh rate: 100 Hz | Product colour: Black | Pivot: Yes | Stand included: Yes | Storage temperature (T-T): -20 - 60 °C | Dell Display Manager (DDM) compatibility: Yes | Power consumption (max): 74 W | Width (without stand): 610.7 mm | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | Native aspect ratio: 16:9 | Viewing angle, vertical: 178° | Supported video modes: 576p | Viewable size, vertical: 33.6 cm | DisplayPort version: 1.2 | Swivelling: Yes | Supported video modes: 480p | Supported video modes: 1080p | Pixel density: 81.57 ppi | Viewable size, horizontal: 59.8 cm | Input current: 1.5 A | Built-in USB hub: Yes | Supported video modes: 720p | Flicker-free technology: Yes | USB Type-C downstream ports quantity: 1 | Display brightness (typical): 300 cd/m² | Weight (without stand): 4.03 kg | DisplayPorts quantity: 1 | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | HD type: Full HD | Horizontal scan range: 30 - 83 kHz | AC input voltage: 100 - 240 V | Response time (fast): 5 ms | HDMI: Yes | Panel type: IPS | Supported graphics resolutions: 1280 x 1024 (SXGA) | Energy consumption (SDR) per 1000 hours: 16 kWh | Cables included: DisplayPort | USB Power Delivery (USB PD): Yes | VESA mounting: Yes | Tilt adjustment: Yes | Doesn't contain: Arsenic | AC (power) in: Yes | Bezel width (top): 6.4 mm | Doesn't contain: Mercury | Supported graphics resolutions: 640 x 480 (VGA) | Tilt angle range: -5 - 21° | HDMI version: 1.4 | Sustainability certificates: ENERGY STAR | Sustainability certificates: TCO | Plug and Play: Yes | Viewable size diagonal: 68.6 cm | Swivel angle range: -45 - 45° | Front bezel colour: Black | HDCP: Yes | HDMI ports quantity: 1 | Sustainability compliance: Yes | USB Type-A downstream ports quantity: 3 | Cables included: USB | Windows operating systems supported: Yes | Doesn't contain: PVC/BFR | Package weight: 8.47 kg | Power consumption (standby): 0.3 W | Feet colour: Grey | Depth (without stand): 50 mm | Bezel width (bottom): 1.2 cm | Built-in camera: No | Number of USB Type-B upstream ports quantity: 1 | Display technology: LCD | Height (with stand): 384.6 mm | Windows operating systems supported: Windows 10 | Cables included: AC | Supported graphics resolutions: 1600 x 900 | Response time: 8 ms | Quick start guide: Yes | Sustainability certificates: RoHS | Supported graphics resolutions: 1024 x 768 (XGA) | USB cable length: 1.8 m | Supported graphics resolutions: 720 x 400 | Sustainability certificates: TÜV mark | Supported graphics resolutions: 1152 x 864 (XGA+) | Contrast ratio (typical): 1500:1 | Supported graphics resolutions: 1280 x 720 (HD 720) | Energy efficiency class (SDR): D | Warnings: Unplug the monitor from the power source before cleaning. | Warnings: Do not

disassemble the monitor casing to avoid risk of electric shock. | Warnings: Place the monitor on a flat

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

and stable surface to avoid tipping and damage.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950