



HP E24m G4 FHD USB-C Conferencing Monitor

Model: 40Z32AA#ABB

Manufacturer: HEWLETT-PACKARD

EAN: 195908730736

Product Code: 47352

R5,149

Bundled software: HP Display Center HP Display Manager | Certification: Australian-New Zealand MEPS BIS BSMI CB CCC CE CECP CEL cTUVus EAC E-standby FCC ISO 9241-307 KC/KCC NOM PSB RCM SEPA TUV-S VCCI Vietnam MEPS WEEE ISC Mexico Energy ICE UAE TGM TUV-GS Ukraine certificates NRCS of South Africa Belarus Energy CEL Grade 2 | Adjustable height (max): 15 cm | General Product Safety Regulation (GPSR) URL: <https://support.hp.com/gb-en/product/setup-user-guides/hp-deskjet-2700-all-in-one-printer-series/model/31598160?sku=5AR83B&serialnumber=5AR83B> | Infrared (IR) sensor: Yes | UNSPSC-code: 43211902 | Total carbon emissions, w/o use phase (kg of CO₂e): 4 | HDMI: Yes | Low Blue Light technology: Yes | HP segment: Business | Surface hardness: 3H | Pixel density: 93 ppi | Compliance certificates: CB | Compliance certificates: EAC | Feet colour: Silver | HP GTIN (EAN/UPC): 888182569252, 888182569351 | Carbon emissions, end-of-life (kg of CO₂e): 2 | Compliance certificates: WEEE | Compliance certificates: RCM | Compliance certificates: BIS | Compliance certificates: Federal Communications Commission (FCC) | USB Power Delivery up to: 65 W | Sustainable technologies and materials: Mercury free | Compliance

certificates: CE | Anti-glare screen: Yes | Compliance certificates: BSMI | Compliance certificates:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

CECP | Compliance certificates: Norma Oficial Mexicana (NOM) | Power consumption (max): 150 W | Width (without stand): 539.4 mm | Compliance certificates: VCCI | Compliance certificates: KCC | Compliance certificates: CEL | Compliance certificates: CCC | USB Power Delivery (USB PD): Yes | Compliance certificates: cTUVus | Display bezel technology: Micro-Edge | Number of speakers: 2 | Operating relative humidity (H-H): 5 - 95% | Depth (without stand): 47 mm | USB Type-C DisplayPort Alternate Mode: Yes | Headphone outputs: 1 | Built-in speaker(s): Yes | Flicker-free technology: Yes | USB Type-C downstream ports quantity: 1 | Power consumption (standby): 0.5 W | Built-in camera: Yes | Package width: 603 mm | Tilt adjustment: Yes | Audio output: Yes | HDMI version: 1.4 | Display diagonal (metric): 60.5 cm | Depth: 47 mm | Energy efficiency class (HDR): Not available | Carbon emissions, logistics (kg of CO2e): 2 | Height (without stand): 355.6 mm | Sustainability certificates: ENERGY STAR | Swivelling: Yes | Height: 355.6 mm | Vertical scan range: 50 - 75 Hz | Power supply type: Internal | Viewable size, vertical: 29.6 cm | Pivot: Yes | Stand included: Yes | Swivel angle range: -45 - 45° | sRGB coverage (typical): 99% | Audio input: Yes | Energy consumption (SDR) per 1000 hours: 18 kWh | Headphone connectivity: 3.5 mm | Headphone out: Yes | Display number of colours: 16.7 million colours | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | VESA mounting: Yes | Cables included: USB Type-C to USB Type-C | Cables included: AC | Viewing angle, vertical: 178° | Horizontal scan range: 30 - 85 kHz | Viewable size, horizontal: 52.7 cm | Detachable stand: Yes | Colour depth: 8 bit | Digital horizontal frequency: 30 - 85 kHz | Backlight type: Edge LED | Carbon emissions, manufacturing (kg of CO2e): 30 | Energy efficiency class (SDR): E | Colour gamut: 99% | Digital vertical frequency: 50 - 75 Hz | Touchscreen: No | Package height: 421 mm | Panel type: IPS | Sustainability compliance: Yes | Pivot angle: -90 - 90° | Storage relative humidity (H-H): 20 - 80% | Built-in USB hub: Yes | Height adjustment: Yes | Package depth: 192 mm | Megapixel (approx.): 5 MP | Market positioning: Business | Weight (with stand): 7.39 kg | European Product Registry for Energy Labelling (EPREL) code: 846610 | HDMI ports quantity: 1 | Total carbon footprint (kg of CO2e): 40 | On Screen Display (OSD): Yes | Maximum refresh rate: 75 Hz | Harmonized System (HS) code: 85285210 | Colour gamut standard: sRGB | Contrast ratio (typical): 1000:1 | Pixel pitch: 0.2745 x 0.2745 mm | Width: 539.4 mm | Panel mounting interface: 100 x 100 mm | USB Type-A downstream ports quantity: 4 | RMS rated power: 10 W | Power consumption (typical): 37 W | Display technology: LCD | Display resolution: 1920 x 1080 pixels | AC input frequency: 50/60 Hz | Product colour: Black | Screen shape: Flat | HD type: Full HD | Response time: 5 ms | Native aspect ratio: 16:9 | Tilt angle range: -5 - 23° | Display brightness (typical): 300 cd/m² | DisplayPorts quantity: 1 | Weight: 7.39 kg | Ethernet LAN (RJ-45) ports: 1 | Aspect ratio: 16:9 | Quick start guide: Yes | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1680 x 1050 (WSXGA+) | Supported graphics resolutions: 1024 x 768 (XGA) | Supported graphics resolutions: 1440 x 900 (WXGA+) |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 1280 x 1024 (SXGA) | AC input voltage: 100 - 240 V | Supported graphics resolutions: 720 x 400 | Supported graphics resolutions: 1280 x 800 | Cable lock slot: Yes | Height (with stand): 530.7 mm | Built-in microphone: Yes | Display diagonal: 60.5 cm (23.8") | Depth (with stand): 216 mm | Display surface: Matt | HDCP: Yes | Width (with stand): 539.4 mm | DisplayPort version: 1.2 | Supported graphics resolutions: 1600 x 900 | Package type: Box | Viewing angle, horizontal: 178° | Package weight: 10.3 kg | Operating temperature (T-T): 5 - 35 °C | Contrast ratio (dynamic): 10000000:1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950