



iiyama ProLite XU2493HSU-B7 computer monitor 60.5 cm (23.8) 1920 x 1080 pixels Full HD LED Black



Model: XU2493HSU-B7

Manufacturer: Iiyama

EAN: 4948570124589

Product Code: 47358

R2,361

Display resolution: 1920 x 1080 pixels | AC input frequency: 50/60 Hz | Product colour: Black | Display diagonal: 60.5 cm (23.8") | Tilt angle range: 22 - 4° | HDCP: Yes | Display brightness (typical): 300 cd/m² | Power consumption (off): 0.3 W | AC input voltage: 100 - 240 V | Native aspect ratio: 16:9 | Cable lock slot: Yes | Display surface: Matt | Width (with stand): 538.5 mm | Energy efficiency class (HDR): Not available | Energy efficiency class (SDR): E | Energy consumption (SDR) per 1000 hours: 18 kWh | Cable lock slot type: Kensington | On Screen Display (OSD) languages: English | On Screen Display (OSD) languages: German | On Screen Display (OSD) languages: Italian | On Screen Display (OSD) languages: Dutch | Power supply type: Internal | Cable management: Yes | On Screen Display (OSD) languages: Japanese | Panel mounting interface: 100 x 100 mm | On Screen Display

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(OSD) languages: Russian | On Screen Display (OSD) languages: Czech | Touchscreen: No | On Screen Display (OSD) languages: French | Display number of colours: 16.7 million colours | Pixel pitch: 0.275 x 0.275 mm | On Screen Display (OSD) languages: Polish | sRGB coverage (typical): 96% | Display diagonal (metric): 60.5 cm | NTSC coverage (typical): 72% | On Screen Display (OSD): Yes | Energy efficiency scale: A to G | Contrast ratio (typical): 1300:1 | Low Blue Light technology: Yes | Quick start guide: Yes | Response time: 1 ms | Built-in USB hub: Yes | Built-in camera: No | USB hub version: 2.0 | Package type: Box | Package height: 405 mm | Package depth: 126 mm | Viewing angle, horizontal: 178° | Maximum refresh rate: 100 Hz | RMS rated power: 2 W | Weight (with stand): 3 kg | Panel type: IPS | HDMI: Yes | DisplayPorts quantity: 1 | HDMI version: 1.4 | Height (with stand): 393 mm | Built-in speaker(s): Yes | Screen shape: Flat | Depth (with stand): 178.5 mm | On Screen Display (OSD) languages: Spanish | VESA Adaptive Sync support: Yes | HDMI ports quantity: 1 | Viewable size, vertical: 52.7 cm | HD type: Full HD | DisplayPort version: 1.2 | Contrast ratio (dynamic): 80000000:1 | Power consumption (typical): 18 W | Display technology: LED | Tilt adjustment: Yes | Viewable size, horizontal: 29.6 cm | Headphone out: Yes | Flicker-free technology: Yes | Number of speakers: 2 | Market positioning: Business | Viewing angle, vertical: 178° | Package weight: 4.2 kg | Horizontal scan range: 30 - 110 kHz | Power consumption (standby): 0.5 W | Wall mountable: Yes | Package width: 615 mm | VESA mounting: Yes | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Warnings: Unplug the monitor from the power source before cleaning. | European Product Registry for Energy Labelling (EPREL) code: 2025213 | Colour gamut standard: NTSC

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950