



AG Neovo QM-4302 Digital signage flat panel 108 cm (42.5) IPS 400 cd/m 4K Ultra HD Black 24/7



Model: QM-4302

Manufacturer: AG NEOVO

EAN: 4710739597035

Product Code: 47369

R11,435

Certification: FCC, CE, LVD, UKCA, WEEE, RoHS, REACH, EAC, ICES-003(Issue 7) | HD type: 4K Ultra HD | Storage temperature (T-T): -20 - 60 °C | Operating temperature (T-T): 0 - 40 °C | Package height: 673 mm | Built-in speaker(s): Yes | USB playback: Yes | Purpose: Universal | Surface hardness: 3H | Response time: 5 ms | Product colour: Black | Power consumption (off): 0.3 W | Energy efficiency scale: A to G | USB port: Yes | Computer system: No | Package depth: 141 mm | Cable lock slot type: Kensington | Native aspect ratio: 16:9 | Anti-glare screen: Yes | Package width: 1070 mm | Vertical scan range: 23 - 76 Hz | Remote (IR) output: 1 | Product design: Digital signage flat panel | Number of built-in speakers: 2 | DVI port: No | Remote control included: Yes | Wi-Fi: No | VESA mounting: Yes | Operating hours (hours/days): 24/7 | USB version: 2.0 | HDMI ports quantity: 3

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

| Ethernet LAN (RJ-45) ports: 1 | Contrast ratio (typical): 4500:1 | Energy efficiency class (SDR): G | Display technology: IPS | RMS rated power: 2 x 10 W | Storage relative humidity (H-H): 10 - 90% | Built-in processor: No | Batteries included: Yes | USB ports quantity: 1 | Display depth: 63.5 mm | Orientation: Horizontal | Horizontal scan range: 15 - 136 kHz | European Product Registry for Energy Labelling (EPREL) code: 1090616 | Power consumption (standby): 0.5 W | Warnings: The product should be disposed of by specialist disposal facilities for electronic equipment. | Display brightness: 400 cd/m² | Display weight: 10.8 kg | Display height: 561.2 mm | Power consumption (typical): 102 W | HDMI version: 2.0 | Display diagonal (metric): 108 cm | AC input voltage: 100 - 240 V | Panel type: IPS | Viewing angle, horizontal: 178° | Placement supported: Indoor | Mounting type: Wall | Pixel pitch: 0.245 x 0.245 mm | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Low Voltage Directive (LVD) | Ethernet LAN: Yes | Panel mounting interface: 200 x 200 mm | Display width: 973 mm | Energy consumption (SDR) per 1000 hours: 102 kWh | Haze rate: 1% | Touchscreen: No | PC Audio in: Yes | Operating relative humidity (H-H): 20 - 80% | Display resolution: 3840 x 2160 pixels | Viewing angle, vertical: 178° | Cables included: AC | RS-232 interface: Yes | Display number of colours: 1.07 billion colours | Package weight: 13.6 kg | Cables included: HDMI | AC input frequency: 50 - 60 Hz | Compliance certificates: REACH | VGA (D-Sub) input ports: 1 | Warnings: The monitor contains substances hazardous to health, including mercury avoid contact with damaged parts. | Display diagonal: 108 cm (42.5") | Compliance certificates: WEEE | Warnings: Do not open the appliance housing, risk of electric shock.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950