



## **AG Neovo PM-3202 Signage Display Digital signage flat panel 81.3 cm (32) TFT 350 cd/m Full HD Black 16/7**

Model: PM-3202

Manufacturer: AG NEOVO

EAN: 4710739597028

Product Code: 47370

---

## **R7,169**

---

Built-in speaker(s): Yes | Display technology: TFT | Power consumption (typical): 42 W | Purpose: Universal | Computer system: No | Built-in processor: No | Number of built-in speakers: 2 | Operating hours (hours/days): 16/7 | Ethernet LAN: Yes | DVI port: No | Microphone in: Yes | Vertical scan range: 48 - 85 Hz | HDMI version: 2.0 | Surface hardness: 3H | Energy efficiency class (SDR): G | Remote control included: Yes | RMS rated power: 20 W | HDMI ports quantity: 3 | Panel type: VA | RS-232 interface: Yes | LED backlighting type: LED | Power consumption (standby): 0.5 W | On Screen Display (OSD): Yes | HDMI input ports quantity: 3 | USB version: 2.0 | Wi-Fi: No | VESA mounting: Yes | Noise reduction: Yes | USB port: Yes | Display brightness: 350 cd/m<sup>2</sup> | Panel mounting interface: 200

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

x 200 mm | USB ports quantity: 1 | Haze rate: 2% | Remote (IR) input: 1 | Cables included: HDMI | Horizontal scan range: 28 - 92 kHz | Touchscreen: No | Panel mounting interface: 100 x 100 mm | Pixel pitch: 0.364 x 0.364 mm | Power adapter included: Yes | Product design: Digital signage flat panel | Contrast ratio (typical): 4000:1 | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Warnings: Unplug the monitor from the power source before cleaning. | Display diagonal: 81.3 cm (32") | Response time: 5 ms | Quick start guide: Yes | Operating temperature (T-T): 0 - 40 °C | Storage temperature (T-T): 20 - 80 °C | Ethernet LAN (RJ-45) ports: 1 | Product colour: Black | Viewing angle, vertical: 178° | Viewing angle, horizontal: 178° | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 1000 Mbit/s | AC input voltage: 100 - 240 V | Power consumption (off): 0.3 W | HD type: Full HD | Display resolution: 1920 x 1080 pixels | AC input frequency: 50 - 60 Hz | Storage relative humidity (H-H): 10 - 90% | Display number of colours: 16.7 million colours | Operating relative humidity (H-H): -20 - 60%

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950