



AG Neovo NSD-5503 - UHD 4K digital advertising display



Model: NSD-5503

Manufacturer: AG NEOVO

EAN: 4710739598094

Product Code: 47372

R17,400

Display brightness (typical): 500 cd/m² | Display resolution: 3840 x 2160 pixels | Product colour: Black | AC input frequency: 50 - 60 Hz | AC input voltage: 100 - 240 V | Display diagonal: 138.7 cm (54.6") | HDMI version: 2.0 | RS-232 interface: Yes | Vertical scan range: 24 - 60 Hz | Warnings: Do not open the appliance housing, risk of electric shock. | Depth (without stand): 38,6 mm | HDMI: Yes | Storage temperature (T-T): -20 - 60 °C | Remote control type: Y | Power consumption (standby): 0.5 W | Batteries included: Yes | Energy efficiency scale: A to G | Width (without stand): 1239.7 mm | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 1 | Energy efficiency class: G | HD type: 4K Ultra HD | Number of speakers: 2 | Cables included: AC | Height (without stand): 712,5 mm | Cables included: HDMI | Warnings: The monitor contains substances hazardous to health, including mercury avoid contact with damaged parts. | VESA mounting: Yes | RMS rated power: 2 x 10 W | Screen shape: Flat | Built-in speaker(s): Yes | Operating relative humidity (H-H): 20 - 80% | HDMI ports quantity: 3 | Panel type: VA | Weight (without stand): 17.6 kg | Audio out (mini jack): 1 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Response time: 5 ms | Horizontal scan range: 18 - 135 kHz | Compliance certificates: Low Voltage Directive (LVD) | Viewing angle, vertical: 178° | Pixel pitch: 0.315 x 0.315 mm | Compliance certificates: ICES-003 Issue 7 | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: WEEE | USB 2.0 connectors: 2 | Compliance certificates: Federal Communications Commission (FCC) | Panel mounting interface: 300 x 400 mm | Compliance certificates: BSMI | Viewing angle, horizontal: 178° | Compliance certificates: REACH | Contrast ratio (dynamic): 4000:1 | Power consumption (typical): 89 W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950