



Philips E Line 241E1SCA/00 computer monitor 59.9 cm (23.6) 1920 x 1080 pixels Full HD LCD Black



Model: 241E1SCA/00

Manufacturer: PHILIPS

EAN: 8712581759377

Product Code: 47383

R2,566

Certification: CE Mark, CU-EAC, TUV-BAUART | TV tuner integrated: No | Aspect ratio: 16:9 | Display brightness (typical): 250 cd/m² | Tilt angle range: -5 - 20° | Display diagonal: 59.9 cm (23.6") | Product colour: Black | Windows operating systems supported: Windows 8.1 | Operating altitude: 0 - 3658 m | Response time: 4 ms | Supported graphics resolutions: 1920 x 1080 (HD 1080) | LED indicators: Operation | AC input voltage: 100 - 240 V | LED indicators: Stand-by | Native aspect ratio: 16:9 | Display resolution: 1920 x 1080 pixels | Manual: Yes | AC input frequency: 50 - 60 Hz | Operating relative humidity (H-H): 20 - 80% | HDCP: Yes | Package width: 595 mm | Height (with stand): 413 mm | Viewing angle, vertical: 178° | Horizontal scan range: 30 - 85 kHz | Windows operating systems supported: Windows 10 | Package type: Box | Package weight: 5.37 kg | Display

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

surface: Matt | Cable lock slot type: Kensington | Warnings: Unplug the monitor from the power source before cleaning. | Storage temperature (T-T): -20 - 60 °C | Package depth: 154 mm | Width (with stand): 536 mm | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | HD type: Full HD | Mac operating systems supported: Mac OS X 10.5 Leopard | Mac operating systems supported: Mac OS X 10.13 High Sierra | Mac operating systems supported: Mac OS X 10.11 El Capitan | Screen shape: Curved | Mac operating systems supported: Mac OS X 10.14 Mojave | Mac operating systems supported: Mac OS X 10.6 Snow Leopard | Mac operating systems supported: Mac OS X 10.4 Tiger | Mac operating systems supported: Mac OS X 10.2 Jaguar | Mac operating systems supported: Mac OS X 10.10 Yosemite | Mac operating systems supported: Mac OS X 10.12 Sierra | Mac operating systems supported: Mac OS X 10.7 Lion | Operating temperature (T-T): 0 - 40 °C | Mac operating systems supported: Mac OS X 10.8 Mountain Lion | Mac operating systems supported: Mac OS X 10.1 Puma | Power consumption (off): 0.3 W | Colour gamut standard: sRGB | Depth (with stand): 202 mm | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 7 | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Mac operating systems supported: Mac OS X 10.9 Mavericks | Mac operating systems supported: Mac OS X 10.3 Panther | Mac operating systems supported: Mac OS X 10.0 Cheetah | Viewing angle, horizontal: 178° | Compliance certificates: RoHS | Display number of colours: 16.7 million colours | Cable lock slot: Yes | Pixel pitch: 0.272 x 0.272 mm | Packaging recyclability rate: 100% | Supported video modes: 1080p | Cables included: AC | Low Blue Light technology: Yes | Cables included: HDMI | Component video sync: Separate Sync | Panel type: VA | Number of speakers: 2 | Energy efficiency scale: A to G | Width (without stand): 536 mm | Weight (without stand): 2.86 kg | Viewable size, vertical: 29.3 cm | Height adjustment: No | NTSC coverage (typical): 83.87% | Display diagonal (metric): 59.9 cm | HDMI: Yes | Flicker-free technology: Yes | Audio input: Yes | Maximum refresh rate: 75 Hz | Non-operating altitude: 0 - 12192 m | Energy efficiency class (SDR): E | LowBlue mode: Yes | Tilt adjustment: Yes | Depth (without stand): 66 mm | Dynamic contrast ratio marketing name: SmartContrast | Panel mounting interface: 100 x 100 mm | Heavy metals free: Pb (lead) | Heavy metals free: Hg (mercury) | Cables included: Audio (3.5mm) | Built-in camera: No | Plug and Play: Yes | Digital vertical frequency: 48 - 76 Hz | Backlight type: W-LED | Display technology: LCD | Regulatory Approvals: CE Mark CU-EAC TUV-BAUART | PC Audio in: Yes | sRGB coverage (typical): 100.78% | Touchscreen: No | Haze rate: 25% | Display sRGB: Yes | Power consumption (typical): 27.9 W | Weight (with stand): 3.54 kg | Height (without stand): 322 mm | On Screen Display (OSD): Yes | Mean time between failures (MTBF): 50000 h | Energy consumption (SDR) per 1000 hours: 22 kWh | Pixel density: 93 ppi | AMD FreeSync: Yes | On Screen Display (OSD) languages: Portuguese | External power adapter: Yes | On Screen Display (OSD) languages:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Traditional Chinese | On Screen Display (OSD) languages: French | On Screen Display (OSD) languages: Korean | On Screen Display (OSD) languages: Japanese | Contrast ratio (typical): 3000:1 | On Screen Display (OSD) languages: Ukrainian | On Screen Display (OSD) languages: Finnish | On Screen Display (OSD) languages: Russian | On Screen Display (OSD) languages: Czech | On Screen Display (OSD) languages: Polish | On Screen Display (OSD) languages: German | On Screen Display (OSD) languages: Italian | On Screen Display (OSD) languages: Dutch | Built-in USB hub: No | Package height: 475 mm | VGA (D-Sub) ports quantity: 1 | On Screen Display (OSD) languages: Spanish | On Screen Display (OSD) languages: Greek | On Screen Display (OSD) languages: Simplified Chinese | Vertical scan range: 48 - 76 Hz | On Screen Display (OSD) languages: English | Anti-glare screen: Yes | On Screen Display (OSD) languages: Swedish | On Screen Display (OSD) languages: Hungarian | Power supply type: External | Digital horizontal frequency: 30 - 85 kHz | HDMI ports quantity: 1 | DDC/CI: Yes | On/off switch: Yes | On Screen Display (OSD) languages: Turkish | Picture enhancement: SmartImage game | Exterior finish type: Textured | Market positioning: Home | Surface hardness: 3H | Colour gamut: 87% | RMS rated power: 6 W | Harmonized System (HS) code: 85285210 | Component video sync: Sync-on-green (SOG) | DVI port: No | VESA mounting: Yes | Headphone out: Yes | Screen curvature rating: 1500R | Headphone outputs: 1 | Viewable size, horizontal: 52.1 cm | Built-in speaker(s): Yes | Doesn't contain: Mercury | Doesn't contain: PVC/BFR | Power consumption (standby): 0.5 W | Energy efficiency class (old): F | Stand included: Yes | Screen curvature: 150 cm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950