



Philips S Line 242S9JML/00 LED display 61 cm (24) 1920 x 1080 pixels Full HD LCD Black

Model: 242S9JML/00

Manufacturer: PHILIPS

EAN: 8712581796464

Product Code: 47387

R3,307

Bundled software: SmartControl | Compatible operating systems: Windows 11 / 10 / 8.1 / 8 / 7 Mac OS X | European Product Registry for Energy Labelling (EPREL) code: 1291734 | Compliance certificates: RoHS | Adjustable height (max): 13 cm | Warnings: Unplug the monitor from the power source before cleaning. | Colour gamut standard: sRGB | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Display brightness (typical): 300 cd/m² | Display diagonal: 61 cm (24") | Height (with stand): 484 mm | Display resolution: 1920 x 1080 pixels | Response time: 4 ms | DisplayPorts quantity: 1 | Operating relative humidity (H-H): 20 - 80% | Package weight: 7.15 kg | DisplayPort version: 1.2 | Screen shape: Flat | AC input frequency: 50 - 60 Hz | Viewing angle, vertical: 178° | LED indicators: Operation | Native aspect ratio: 16:9 | Depth (with stand): 205 mm | Tilt angle range: -5 - 25° | Operating altitude: 0 - 3658 m | Contrast ratio (dynamic): 50000000:1 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Product colour: Black | Storage temperature (T-T): -20 - 60 °C | Width (with stand): 539 mm | HDCP: Yes | LED indicators: Stand-by | Viewing angle, horizontal: 178° | HD type: Full HD | AC input voltage: 100 - 240 V | Power consumption (off): 0.3 W | Cable lock slot type: Kensington | Power consumption (PowerSave): 12 W | Cable lock slot: Yes | Pixel pitch: 0.2745 x 0.2745 mm | Display number of colours: 16.7 million colours | Operating temperature (T-T): 0 - 40 °C | NTSC coverage (typical): 80% | Plug and Play: Yes | Maximum refresh rate: 75 Hz | VESA Adaptive Sync support: Yes | Package height: 420 mm | Backlight type: W-LED | USB Power Delivery (USB PD): Yes | Cables included: DisplayPort | Height adjustment: Yes | Number of speakers: 2 | Heavy metals free: Hg (mercury) | Display diagonal (metric): 60.5 cm | Sustainability certificates: ENERGY STAR | Sustainability certificates: TCO | Swivelling: Yes | Number of upstream ports: 1 | DVI-D ports quantity: 1 | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | Weight (without stand): 3.09 kg | USB upstream port type: USB Type-B | Doesn't contain: Mercury | LowBlue mode: Yes | Digital vertical frequency: 48 - 75 Hz | Cables included: AC | VESA mounting: Yes | Tilt adjustment: Yes | Audio output: Yes | Package depth: 139 mm | Pivot angle: -90 - 90° | Power consumption (standby): 0.4 W | Low Blue Light technology: Yes | Built-in camera: No | VGA (D-Sub) ports quantity: 1 | Packaging recyclability rate: 100% | Power supply type: Internal | Mean time between failures (MTBF): 70000 h | Picture enhancement: SmartImage | Display sRGB: Yes | Width (without stand): 539 mm | Surface hardness: 3H | Dynamic contrast ratio marketing name: SmartContrast | Exterior finish type: Textured | Flicker-free technology: Yes | Front bezel colour: Black | Swivel angle range: -180 - 180° | HDCP version: 1.4 | Component video sync: Sync-on-green (SOG) | PC Audio in: Yes | sRGB coverage (typical): 99% | Touchscreen: No | EasyRead mode: Yes | Display technology: LCD | Built-in USB hub: Yes | HDMI: Yes | Market positioning: Business | Feet colour: Black | Package width: 730 mm | Viewable size, vertical: 29.6 cm | Sustainability compliance: Yes | Cables included: HDMI | Doesn't contain: PVC/BFR | Depth (without stand): 55 mm | Component video sync: Separate Sync | Pixel density: 93 ppi | Energy consumption (SDR) per 1000 hours: 14 kWh | Number of USB Type-B upstream ports quantity: 1 | Haze rate: 25% | Power consumption (typical): 15 W | Panel type: VA | Weight (with stand): 4.85 kg | HDMI version: 1.4 | On Screen Display (OSD) languages: English | Height (without stand): 324 mm | On Screen Display (OSD) languages: Polish | Manual: Yes | On Screen Display (OSD) languages: Greek | Regulatory Approvals: CB CE Mark CU-EAC EAEU RoHS FCC Class B ICES-003 SEMKO TUV Ergo TUV/GS | On Screen Display (OSD) languages: Ukrainian | On Screen Display (OSD) languages: Finnish | Anti-glare screen: Yes | On Screen Display (OSD) languages: Simplified Chinese | On Screen Display (OSD) languages: Portuguese | On Screen Display (OSD) languages: Russian | On Screen Display (OSD) languages: Czech | On Screen Display (OSD) languages: Swedish | On Screen Display (OSD) languages: Hungarian | On Screen Display (OSD) languages: Japanese | On Screen Display

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(OSD) languages: Turkish | On Screen Display (OSD) languages: German | On Screen Display (OSD) languages: Italian | On Screen Display (OSD) languages: Dutch | DVI port: Yes | Built-in speaker(s): Yes | Stand included: Yes | Pivot: Yes | Viewable size, horizontal: 52.7 cm | Panel mounting interface: 100 x 100 mm | On Screen Display (OSD) languages: Traditional Chinese | On Screen Display (OSD) languages: French | On Screen Display (OSD) languages: Korean | Product post-consumer recycled plastic: 85% | Non-operating altitude: 3658 - 12192 m | Digital horizontal frequency: 30 - 85 kHz | USB Type-A downstream ports quantity: 4 | Colour depth: 8 bit | Contrast ratio (typical): 3000:1 | RMS rated power: 2 W | On Screen Display (OSD) languages: Spanish | HDMI ports quantity: 1 | DDC/CI: Yes | Energy efficiency class (SDR): D

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950