



Philips 1000 series 24E1N1100A/00 LED display 60.5 cm (23.8) 1920 x 1080 pixels Full HD LCD Black



Model: 24E1N1100A/00

Manufacturer: PHILIPS

EAN: 8712581804244

Product Code: 47391

R1,716

Compatible operating systems: Mac OS X Windows 11 / 10 | Power consumption (standby): 0.5 W | VESA mounting: Yes | On Screen Display (OSD) languages: Portuguese | On Screen Display (OSD) languages: Simplified Chinese | Power supply type: External | On Screen Display (OSD) languages: Swedish | On Screen Display (OSD) languages: Hungarian | On Screen Display (OSD) languages: Japanese | AMD FreeSync: No | On Screen Display (OSD) languages: Spanish | On Screen Display (OSD) languages: Greek | On Screen Display (OSD) languages: Ukrainian | On Screen Display (OSD) languages: Finnish | On Screen Display (OSD) languages: Russian | On Screen Display (OSD) languages: Czech | On Screen Display (OSD) languages: English | Backlight type: W-LED | VGA (D-Sub) ports quantity: 1 | On Screen Display (OSD) languages: Turkish | Doesn't contain: PVC | Doesn't

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

contain: Mercury | On Screen Display (OSD) languages: Polish | Display sRGB: Yes | Panel mounting interface: 100 x 100 mm | Panel type: IPS | Tilt adjustment: Yes | Audio output: Yes | Non-operating altitude: 3658 - 12192 m | Number of speakers: 2 | Display diagonal (metric): 60.5 cm | Audio input: Yes | Doesn't contain: BFR | Viewable size, vertical: 29.6 cm | Sustainability compliance: Yes | DDC/CI: Yes | On Screen Display (OSD): Yes | On Screen Display (OSD) languages: German | On Screen Display (OSD) languages: Italian | On Screen Display (OSD) languages: Dutch | Number of OSD languages: 21 | Market positioning: Home | Contrast ratio (typical): 1300:1 | Touchscreen: No | Viewable size, horizontal: 52.7 cm | Energy efficiency class (SDR): D | On Screen Display (OSD) languages: Traditional Chinese | On Screen Display (OSD) languages: French | On Screen Display (OSD) languages: Korean | Display technology: LCD | Built-in speaker(s): Yes | Built-in USB hub: No | Energy efficiency class (HDR): Not available | Anti-glare screen: Yes | Weight (with stand): 2.92 kg | Component video sync: Separate Sync | Surface hardness: 3H | Low Blue Light technology: Yes | Mean time between failures (MTBF): 50000 h | Flicker-free technology: Yes | HDCP version: 1.4 | HDMI: Yes | Maximum refresh rate: 100 Hz | LowBlue mode: Yes | EasyRead mode: Yes | Picture enhancement: SmartImage game | Heavy metals free: Hg (mercury) | Height (without stand): 316 mm | Response time (fast): 1 ms | Pixel density: 92.56 ppi | Width (without stand): 542 mm | VESA Adaptive Sync support: Yes | Depth (without stand): 45 mm | Feet colour: Black | Haze rate: 25% | RMS rated power: 4 W | Dynamic contrast ratio marketing name: Mega Infinity DCR | Plug and Play: Yes | Built-in camera: No | Colour gamut standard: sRGB | Stand included: Yes | Weight (without stand): 2.57 kg | Tilt angle range: -5 - 20° | Display diagonal: 60.5 cm (23.8") | Product colour: Black | Package depth: 124 mm | Viewing angle, horizontal: 178° | Screen shape: Flat | LED indicators: Operation | HD type: Full HD | Vertical scan range: 48 - 60 Hz | Power consumption (off): 0.3 W | Operating altitude: 0 - 3658 m | Cable lock slot type: Kensington | Package height: 370 mm | Storage temperature (T-T): -20 - 60 °C | Width (with stand): 542 mm | NVIDIA G-SYNC: No | Package width: 610 mm | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | AC input voltage: 100 - 240 V | LED indicators: Stand-by | Depth (with stand): 180 mm | Native aspect ratio: 16:9 | Power consumption (typical): 14.5 W | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: ICES | Compliance certificates: RoHS | Cable lock slot: Yes | Pixel pitch: 0.2745 x 0.2745 mm | Compliance certificates: BSMI | Compliance certificates: EAC | Compliance certificates: VCCI | Manual: Yes | Digital horizontal frequency: 30 - 115 kHz | Operating relative humidity (H-H): 20 - 80% | Display resolution: 1920 x 1080 pixels | AC input frequency: 50/60 Hz | Compliance certificates: cTUVus | Package weight: 4.68 kg | Display brightness (typical): 300 cd/m² | Response time: 4 ms | Cables included: HDMI | HDMI version: 1.4 | Display number of colours:

16.7 million colours | Operating temperature (T-T): 0 - 40 °C | Warnings: Do not disassemble the

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

monitor casing to avoid risk of electric shock. | HDCP: Yes | Digital vertical frequency: 48 - 100 Hz |
HDMI ports quantity: 1 | Warnings: Unplug the monitor from the power source before cleaning. |
European Product Registry for Energy Labelling (EPREL) code: 1868751 | Cables included: AC |
Height (with stand): 417 mm | Viewing angle, vertical: 178° | Horizontal scan range: 30 - 85 kHz

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950