



Asrock 1U4L- GENOA/2T server barebone AMD SoC LGA 6096 Rack (1U) Grey

Model: 1U4L-GENOA/2T

Manufacturer: ASROCK

EAN: 4710483942518

Product Code: 47410

R44,398

PCI Express x16 (Gen 5.x) slots: 1 | Warnings: The product may contain components that are harmful to health, use caution when handling. | Warnings: Do not throw into regular trash, product requires special disposal. | Warnings: Do not disassemble the unit yourself. | Motherboard chipset: AMD SoC | Number of storage drives supported: 10 | Product colour: Black | Product colour: Grey | BIOS type: UEFI AMI | Supported RDIMM clock speeds: 4800 MHz | Number of fans: 6 fan(s) | On/off switch: Yes | System Management BIOS (SMBIOS) version: 3.5 | Number of 3.5" bays: 4 | Number of main power supplies: 2 | Storage temperature (T-T): -40 - 70 °C | Ethernet interface type: 10 Gigabit Ethernet | ACPI version: 6.4 | BIOS memory size: 256 Mbit | Supported storage drive types: HDD & SSD | Chassis type: Rack (1U) | Memory form factor: 288-pin DIMM | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 4 | Power supply: 750 W | Number of DIMM slots: 8 | PC health monitoring: Voltage | Cooling type: Active | IPMI LAN (RJ-45) port: Yes | Processor socket: LGA 6096 | Number of 2.5" bays:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

4 | Operating temperature (T-T): 10 - 35 °C | PC health monitoring: Fan | Reset button: Yes | Storage relative humidity (H-H): 20 - 90% | PC health monitoring: Temperature | Width: 676.5 mm | Supported storage drive interfaces: M.2, SATA III | Ethernet LAN (RJ-45) ports: 2 | Number of M.2 (M) slots: 2 | Depth: 438 mm | 80 PLUS certification: 80 PLUS Platinum | Plug and Play: Yes | Compatible processor series: AMD EPYC 9004 | Compatible processor series: AMD EPYC 9005 | LED indicators: System | Ethernet LAN: Yes | LAN controller: Intel® X550-AT2 | Supported memory types: DDR5 RDIMM/3DS RDIMM | VGA (D-Sub) ports quantity: 1 | Number of processors supported: 1 | Height: 43.4 mm | On-board graphics card model: Aspeed AST2600

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950