



## ASUS Server Platform RS300- E12-RS4/1+1 450 W 90SF03A1- M00070



Model: 90SF03A1-M00070

Manufacturer: ASUS

EAN: 4711387500378

Product Code: 47429

## R28,999

Certification: BSMI, CE, CB, FCC(Class A) | Warnings: Do not disassemble the unit yourself. | Warnings: The product may contain components that are harmful to health, use caution when handling. | Warnings: Do not throw into regular trash, product requires special disposal. | Weight: 15.2 kg | Maximum internal memory: 128 GB | Number of M.2 (M) slots: 1 | Supported storage drive interfaces: PCIe/NVMe(M Key)/SATA (B+M Key) | On-board graphics card model: Aspeed AST2600 | Memory channels: Dual-channel | Number of SATA III connectors: 8 | Number of processors supported: 1 | Storage temperature (T-T): -40 - 70 °C | Storage relative humidity (H-H): 20 - 90% | Operating temperature (T-T): 10 - 35 °C | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity: 3 | Supported DIMM module capacities: 8GB | Ethernet LAN (RJ-45) ports: 1 | Supported DIMM module capacities: 32GB | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 2 | Supported storage drive types: HDD & SSD | Product colour: Silver | LAN controller: Intel® I210-AT | Number of DIMM slots: 4 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Intel Xeon series: E-2400 | Supported DIMM module capacities: 16GB | On-board graphics card memory: 64 MB | Ethernet LAN: Yes | Supported UDIMM clock speeds: 3600 | Hot-swap HDD bays: Yes | Depth: 497 mm | Height: 44 mm | Chassis type: Rack (1U) | VGA (D-Sub) ports quantity: 2 | Motherboard chipset: Intel C262 | Supported memory types: DDR5 UDIMM | Ethernet interface type: Fast Ethernet | Number of 3.5" bays: 4 | Storage drive sizes supported: 3.5" | Processor socket: LGA 1700 | Storage drive sizes supported: 2.5 | COM ports quantity: 1 | Ethernet interface type: Gigabit Ethernet | Storage drive sizes supported: M.2 | Width: 439.5 mm

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950