



InLine AV Switch manual 2-port, 3x RCA IN/OUT



Model: 89302I

Manufacturer: INLINE

EAN: 4043718303823

Product Code: 474897

R1,027

Flexible signal switching: Switches reliably between two analog AV sources or destinations using a mechanical switch - ideal for older AV systems.

No power supply required: The switch operates completely passively, allowing installations to be realized independently of power sources.

Rugged metal housing: The robust housing protects the technology and ensures long-lasting and safe operation - even in a professional environment.

High compatibility: Universally applicable with analog AV devices such as DVD players, video recorders, cameras or consoles with RCA connection.

Shielded cinch sockets: The shielded AV sockets enable clean signal transmission without external interference.

The InLine® AV switch manual 2-port is a reliable solution for switching analog audio and video signals via 3x cinch (yellow, white, red). The device enables manual selection between two AV sources to one target connection or vice versa - depending on the application requirements.

Switching is purely mechanical via a switch on the top of the device, allowing the switch to be

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

operated independently of an external power supply.

The robust metal housing ensures a high level of stability in daily use, whether in the workshop, laboratory or service area. The AV sockets are fully shielded and assigned 1:1, which ensures clean and stable signal transmission.

Typical applications include switching between different source devices such as DVD players, video recorders, games consoles or cameras on AV receivers, displays or recording devices with an RCA input. The switch is also suitable as a temporary test unit in AV technology or for analyzing errors in signal paths.

Thanks to its compact design, the switch can be integrated to save space and used immediately without any configuration effort.

Number of AV channels:2 inputs / 1 output or vice versa

Connection:9x RCA socket (3x audio left/right + 1x video per channel)

assignment:assigned 1:1

shielding:fully shielded

Casing material:metal

Switching:mechanical via toggle switch

Signal type:analog (composite video + stereo audio)

Power supply:not required