



ASUS ProArt Display PA24ACRV 23.8inch IPS WLED QHD 16:9 75Hz 350cd/m2 5ms HDMI 2xDP 3xUSB 3.2 Gen 1 Type-A USB 3.2 Gen 1 Type-C



Model: 90LM08Y0-B01M70

Manufacturer: ASUS

EAN: 4711387308127

Product Code: 48548

R9,145

The ASUS ProArt PA24ACRV monitor is engineered for creative professionals who demand precision and reliability in their visual workspace. Featuring a 24-inch display with a 2560 x 1440 QHD resolution, it offers exceptional detail and clarity. The monitor covers 100% sRGB and 95% DCI-P3 color gamuts, backed by Delta E?2 color accuracy and CalMAN Verification, ensuring that the colors you see on the screen are true to life and consistent across various mediums.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Ergonomics are at the forefront of the PA24ACRV's design, with height, pivot, swivel, and tilt adjustments available to provide a comfortable viewing experience, no matter the task at hand. The inclusion of ASUS EyeCare Technology further protects against eye strain during long work sessions. For connectivity, the monitor boasts HDMI, DisplayPort, and USB-C ports, along with a built-in USB 3.2 hub, making it a versatile hub for any creative setup.

The ASUS ProArt PA24ACRV is not just a monitor; it's a gateway to precision, comfort, and connectivity, making it the perfect choice for professionals looking to elevate their creative workflow.

Product Description: ASUS ProArt PA24ACRV - LED monitor - QHD - 24" - HDR | Device Type: LED-backlit LCD monitor - 24" | Energy Label QR Code URL: <https://eprel.ec.europa.eu/qr/1829124> | Energy Class: Class E | Features: USB 3.2 hub | Panel Type: IPS | Aspect Ratio: 16:9 | Native Resolution: QHD 2560 x 1440 at 75 Hz | Pixel Pitch: 0.2058 mm | Brightness: 400 cd/m² | Contrast Ratio: 1000:1 / 3000:1 (dynamic) | HDR Capable: DisplayHDR 400 | Response Time: 5 ms (grey-to-grey) | Colour Support: 16.7 million colours | Colour Gamut: 100% sRGB, 95% DCI-P3 | Input Connectors: HDMI, 2xDisplayPort, USB-C | Display Position Adjustments: Height, pivot (rotation), swivel, tilt | Screen Coating: Anti-glare | Voltage: AC 100-240 V (50/60 Hz) | Colour: Black | Dimensions (WxDxH) - with stand (highest position): 53.96 cm x 19.72 cm x 51.51 cm | Weight: 5.6 kg | Environmental Standards: TCO Certified Displays 9, ENERGY STAR Qualified EPEAT Gold | Compliant Standards: VCCI, BSMI, WHQL, CB, PSB, FCC, RoHS, ISO 9241-307, WEEE, PSE Mark, cULus, MEPS, J-MOSS, CEC, UkrSEPRO, KC, ERP, EAC, RCM, ICES 003, TUV low blue light, TUV flicker free, TUV-GS, TUV-Ergo

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950