



Axagon CRE-SM3T USB-A Smart / ID card Flat Reader

Model: CRE-SM3T

Manufacturer: AXAGON

EAN: 8595247908278

Product Code: 490289

R958

Compact desktop Smart card / ID card reader AXAGON CRE-SM3T FlatReader with USB 2.0 interface. It is especially suitable as an ID card reader for use with computers that have a USB input. The most widespread USB-A connector ensures connection to both new and older computers.

Thanks to the Plug&Play function, the reader is immediately operational without the need to install drivers. For further work with the inserted card, just install the appropriate application. The reader is compatible with most national applications for eID (electronic ID cards).

The card reader supports all common contact Smart card formats, chip cards and other cards, including contact bank payment cards or contact electronic ID cards *. Compatibility with all common OS such as Windows, Linux, macOS and Android, allows wide use on desktops and laptops as well as smartphones and tablets.

The smart LED indicator lights up shortly after the activity change, then turns off and doesn't bother

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

the user with unnecessary light. Compact design, high-quality manufacturing, anti-slip pad and long cable ensure easy and trouble-free use.

Input:

- USB 2.0, protocol CCID.
- Backward compatible with USB 1.1.
- Connection to computer via USB 2.0 type A male connector.

For connection to a phone or tablet with a USB-C connector, we recommend a USB-C -> USB-A reduction, e.g. AXAGON RUCM-AFAC. For connection to a phone with a micro-USB connector, we recommend an OTG reduction micro-USB -> USB-A.

Card reader:

- 1 slot supports contact ATM / CAC / ID / IC / SIS cards.
- Supports ISO 7816 Class A, B and C contact Smart cards (5V, 3V and 1.8V).
- Supports ISO 7816, EMV 4.1 (EMV 2000 level 1) standards.
- Supports protocols T=0 and T=1, I2C, SLE 4432/42 (S=10), SLE 4418/28 (S=9).
- PC/SC 2.0 PC Smart Card standard support.
- Microsoft Smart Card for Windows support.
- Supports I2C cards SLE4418, SLE4428, SLE4432, SLE4442, SLE4436, SLE5536, SLE6636, AT88SC1608, AT45D041.
- Microsoft WHQL USB Smart Card Reader compliant.
- FIPS 201 standard compliant.

Other features:

- Microsoft USB-CCID driver compatible.
- Plug and Play support.
- Support power saving mode, automatic switching to power saving mode.
- Powering the reader via USB bus (bus-power).
- A LED indicates computer USB port connection (steady) and data transfer (flashing).
- LED indicators light up shortly after the activity change, then turns off and doesn't bother.
- Anti-slip pad against spontaneous movement on the table.
- Dimensions 89 x 65 x 15mm, cable length 1.3 m.
- Weight 56 g.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Supported operating systems:

- MS Windows 7 / 8.1 / 10 / 11 and later, macOS, Linux and Android.
- to work with the Smart card, it is necessary to install a suitable application on the connected device.

* Note: The reader only supports contact cards that have visible contacts on the surface. The card without contacts is therefore RFID and cannot be used in the reader.

Package contains:

- USB Smart card reader with 1.3 m hardwired cable,
- multilingual manual CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / SK / SWE / TR / UA / BG / CN / ARA,
- packed in a cardboard box with a hanging hole.