



**CLUB3D USB4™
Gen3x2 Type-C,
6-in-1 Hub with
HDMI™ 8K60Hz
or 4K120Hz,
2xUSB Type-
A(10G),
Ethernet
RJ45(2.5G) and
2xUSB Type-C,
1x Data(10G)
and 1xPD3.0
charging 100
watt**

Model: CSV-1599

Manufacturer: CLUB 3D

EAN: 8719214472566

Product Code: 490582

R3,698

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The Club 3D CSV-1599 is a USB4™ Gen3x2 Type-C, 6-in-1 Hub with HDMI™ 8K60Hz or 4K120Hz, 2xUSB Type-A(10G), Ethernet RJ45(2.5G) and 2xUSB Type-C, 1x Data(10G) and 1xPD3.0 charging 100 watt, this adapter is offering an integrated solution for video, data, power and Ethernet. It has a HDMI™ (8K60Hz) for video transmission, 3 USB data ports (2 USB-A 10G, 1 Type-C 10G)for data transmission, a 2.5Gbps Ethernet port for surfing on line. Besides, this adapter is equipped with Type-C PD3.0 Charging port with max 100W power supply. It can work on USB4™, Thunderbolt4, Thunderbolt3 and DP Alt mode (15W is dedicated to the functioning of this product, the rest power(max 85W) will be passed to charge for the host. This 6-in-1 Hub will work on all DP Alt mode supported Type-C hosts

- Max 10Gbps data transmission
- Support 7.5W(5V@1.5A) downstream charging
- Support short-circuit, over-current, over-voltage protection
- 1x USB Type-C Female (for PD 3.0 Charging)
- Support PD3.0 with max 100W PD Charging
- 15W is dedicated to the functioning of this product, the rest power (85W) will be passed to charge for the host
- Support fast role swap of PD3.0, the connected device will not get disconnected while plugging out PD Adapter;
- 2x USB Type-A Female
- 1- USB Type-A port Data 10G, support max 7.5W(5V@1.5A) downstream charging(closest to RJ45)
- 2- USB Type-A port Data 10G, support max 4.5W(5V@900mA) downstream charging
- 3- Support short-circuit, over-current, over-voltage protection
- 4- USB Type-C and 2 USB Type-A ports share max 2.4A(24W) downstream charging
- 1x RJ45 (Gigabit Ethernet)
- Support 10M/100M/1000M/2.5G bandwidth
- Supports twisted pair crossover detection and auto-correction
- Support WOL(Wake-On-LAN), Full Duplex flow(10M/100M/1G/2.5G Rate), Auto-Negotiation
- Light indicator indicates the state, no light when no Internet connected, orange light turns on when network connection is established, green light flashes when transmitting data.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950