



Zyxel DAC10G-1M-ZZ0103F InfiniBand/fibre optic cable SFP+ Black

Model: DAC10G-1M-ZZ0103F

Manufacturer: ZYXEL

EAN: 4718937611843

Product Code: 491635

R1,562

Standard-based design assures compatibility

The ZyXEL transceiver family follows industry standards to assure compatibility with switches from other manufacturers without barrier set by proprietary technologies.

Comprehensive portfolio for different connectivity demands

With ZyXEL's comprehensive Fast, Gigabit and 10 Gigabit transceiver product range, also Direct Attached Cable 1 M/3 M, users can just plug the proper model onto the network to extend the physical coverage.

Hot-swappable design facilitates network maintenance

Independent transceiver design provides the highest network maintenance flexibility. Transceivers can be freely added when required, and infrastructure upgrades or transceiver repairs can be done

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

easily by just replacing the transceiver instead of the whole device.

Bi-directional transceivers maximizes usage of existing fiber plant

Traditional fiber optic networking requires two strands of fiber to accomplish communications, in which one strand is reserved for sending signals, while the other is for receiving. On the other hand, bi-directional, dual-wavelength transceivers can establish communications over just one strand of fiber by using two separate optical wavelengths: one receives and the other transmits signals.

Transmission capacity can be expanded immediately without additional cost laying new fiber.

Supporting Digital Diagnostics Monitoring Interface (DDMI) SFP enhances management capability

The enhanced digital interface enables a real time link to be established between the switch and the SFP transceiver. This enables the switch to access operating parameters within the fiber link. This includes digital features such as soft control and monitoring of SFP I/O signals.

In addition, the DDMI functionality enables the capability to implement digital alarms and warnings.

This feature ensures that the business can be proactive in preventative maintenance of the network and ensure business continuity.