

**CATA Hood GC  
DUAL A 45  
XGWH Canopy  
Energy  
efficiency class  
A Width 45 cm  
820 m/h Touch  
control LED  
White glass**



Model: 02130207

Manufacturer: CATA

EAN: 8422248078290

Product Code: 511127

**R7,258**

Gross depth (mm): 595 | Gross height (mm): 413 | Gross weight: 11 | Gross width (mm): 380 | Net weight: 10.2 | Packing quantity: 1.00 | Tare weight (kg): 0.8 | Volume (m3): 0.0933793 | Number of motors: 1 | Colour of product: White glass | Type: Canopy | Number of speeds: 4 | Intensive speed: Yes | Motor type: BT3 | Control type: Touch control | Energy efficiency class: A | Lamp type: LED | Control panel: Touch Control Panel with authomatic shut-down timer and cleaning filters indicator | Producer product name: GC DUAL A 45 XGWH | Producer product family: Hood | Noise level (max):

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

65 | Noise level (low speed): 50 | Motor rated power: 280 | Auto power off: Yes | Filter cleaning indicator: Yes | Width: 45 | Exhaust connection diameter: 15/ 12.5 | Height: 30 | Depth: 25 | Washable filter: Yes | Dishwasher proof filter: Yes | Removable filter: Yes | Handheld remote control: No | Grease filter type: Metallic | Lamps quantity: 2 | WEE classification: CL109:4:2017-04-01 | Paper/Pasteboard: 800 | Embeeded battery: No | WEEE tax: Yes | Maximum extraction power according to EN 61591: 820 | Lighting efficiency class: C | Fluid dynamic efficiency class: A | Grease filtering efficiency class: B | Recirculation: Yes | Touch control: Yes | Pressure (Pa): 470 | Minimum distance from gas hob: 65 | Minimum distance from electric hob: 55 | Height (max): 30 | Height (min): 30 | Annual energy consumption: 58.3 | Fluid Dynamic Efficiency (FDE), %: 30.2 | Lighting efficiency (LE): 16.1 | Grease filtering efficiency (GFE), %: 91.2 | Power consumption (standby): 0 | Power consumption (off): 0.3 | Airflow (Minimum speed): 340 | Bulb power: 7 | Motor included: Yes | AC input voltage: 220-240 | Type of extraction: Outlet tube to the exterior / Recirculating | Number of filters: 1 | Power: 287 | AC input frequency: 50 | Carbon filter for recirculation included: No | Palette Qty: 16 | Producer: CATA | Warranty: 36

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950