



**Canon EOS R100
+ RF-S 18-45mm
F4.5-6.3 IS STM
Kit MILC 24.1
MP CMOS 6000 x
4000 pixels
Black**



Model: 6052C013

Manufacturer: CANON

EAN: 4549292214598

Product Code: 513026

R13,220

Gross depth (mm): 88.00 | Gross height (mm): 108.00 | Gross weight: 0.44 | Gross width (mm): 146.30 | Net weight: 0.36 | Packing quantity: 1.00 | Paper/Pasteboard: 50.00 | Plastic (No PET): 30.00 | Tare weight (kg): 0.08 | TI weight (kg): 0.02 | Volume (m3): 0.00 | Classification of battery: CL126:NE:2016-12-09 | Composition of battery: CL127:KT:2016-12-09 | Type of battery: Accumulator | Embeeded battery: Yes | WEEE tax: Yes | WEE classification: CL109:5:2017-04-01 | Palette Qty: 1243 | ISO sensitivity (max): 12800 | Image sensor size (W x H): 2.23x1.49 | Producer product name: 6052C013 | Megapixel: 24.1 | Fastest camera shutter speed: 1/4000 to 30 | Maximum video resolution: 3840 x 2160 | Sensor type: CMOS | Self-timer: 2 | Operating relative humidity (H-H): 0 to 85 | Viewfinder type: 0.39-type OLED electronic viewfinder | White balance: AWB (ambience

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

priority/white priority), Daylight, Shadow, Cloudy, Tungsten, Fluorescent, Flash, Custom, Color temperature setting | HDMI: 1x HDMI (Micro-Type-D connector) | Display aspect ratio: 3:2 | Viewfinder: Yes | Dimensions (WxDxH): 116.3 x 68.8 x 85.5 | Flash exposure compensation: +/- 2 EV in 1/3 step increments | Wi-Fi: Yes | Video formats supported: MPEG-4 AVC/H.264 | USB version: USB 2.0 | Image formats supported: JPEG, RAW | Operating temperature (T-T): 0 to 40 | Flash sync-speed: 1/250 | Video resolutions: 3840 x 2160, 1920 x 1080, 1280 x 720 | ISO sensitivity: 100-12800 | Battery type: Rechargeable lithium-ion battery LP-E17 | Auto focusing (AF) modes: AF+MF available (manual focus adjustment after One Shot AF) Enhance image available under MF (3-10x, in 0.1x increment) | Flash modes: Auto fire from E-TTL II flash measurement (Face Priority/Evaluative/Average) | Display: LCD (TFT) | Battery technology: LP-E17 | Lens mount interface: RF-S | Full HD: Yes | Display diagonal: 3.0 | Focus: Automatic, manual | Shooting modes: Stills: Scene Intelligent Auto Hybrid Auto SCN Special Scene Modes (x10) - Portrait - Landscape - Sports - Panning- Close Shots - Food - Night Portrait - Handheld Night Scene - HDR Backlight Control | Colour of product: Black | Touchscreen: No | Producer product family: EOS R100 Mirrorless Camera + RF-S 18-45mm F4.5-6.3 IS STM Lens | Producer: Canon | Warranty: 12

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950