

Axagon PCEU-430RS PCIe controller 4x ext. USB-A 5Gbps port

Model: PCEU-430RS

Manufacturer: AXAGON

EAN: 8595247908582

Product Code: 514570

R847

The AXAGON PCEU-430RS PCI-Express card adds four external USB-A 5Gbps ports to your desktop computer. The card is designed for fast data transfers at speeds up to 5 Gb/s.

All four USB ports are taken out to the bracket. You can connect four different USB devices such as printers, keyboards, card readers, flash drives, external HDDs, etc.

Reliable power supply of the card is provided from the computer power supply via the SATA power connector. The controller is equipped with a renowned Renesas company chipset with proven seamless compatibility and UASP support.

Input:

• PCI-Express 2.0 interface, compatible with PCI-Express 1.0a / 1.1 / 2.1. / 3.0 / 4.0.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

• Number of 1-Lane lines (x1), compatible with x1 / x4 / x8 / x16 PCIe slots.
• A bandwidth of 1-Lane PCI-Express 2.0 bus up to 5 Gb/s.

Input (power supply):
• SATA 15-pin male power connector.

Output:
• 4x external USB 5Gbps port with USB A-F connectors.
• USB 5Gbps interface - before USB 3.2 Gen 1 / USB 3.0.
• Compatible with USB 3.2 Gen 2, backward compatible with USB 2.0 and USB 1.1.
• Supports transmission rates 5000 / 480 / 12 / 1.5 Mb/s.
• When connected to a PCI-Express bus version 1.0, theor. transmission rate max. 2500 Mb/s.

Other features:
• Full Plug and Play support.
• Supports concurrent activity of SuperSpeed USB, USB 2.0 and USB 1.1 devices.
• Compliant with the final official xHCI specification revision 1.0 by USB-IF.
• Supports UASP (USB Attached SCSI) for faster data transmission in Windows 8 and later.
• Fully supports Hot Plug connecting and disconnecting of USB devices while running.
• Internal SATA power connector for powering the controller from the PC power supply.
• Renesas PD720201 chipset is used.

Supported operating systems:
• MS Windows XP / Vista / 7 / 8 / 8.1 / 10 / 11 and later, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 / 2022 (supported are all 32- and 64-bit Windows OS versions), Linux with kernel 2.6.31 and above.
• Note: Drivers are only installed for Windows XP / Vista / 7. For Linux, Windows 8 / 8.1 / 10, Server 2012 / 2016 / 2019 / 2022 and later versions, no external drivers are required, they are already part of the operating system.

Package contains:
• PCI-Express card with a standard bracket,
• multilingual manual CZ / DE / DK / ENG / ESP / EST / FIN / FR / GR / HR / HU / IT / LT / LV / NL / NOR / PL / PT / RO / SK / SLO / SRB / SWE / TR / UA / ALB / BG / BOS / CN / ARA,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- packed in a cardboard box.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950