

TP-Link Archer 5G AX1800 Wireless Dual- Band Gigabit Router



Model: ARCHER NX200

Manufacturer: TP-LINK

EAN: 8885020621075

Product Code: 606861

R6,325

VPN support: PPTP VPN, IPSec VPN , OpenVPN | Ethernet LAN: Yes | 4G bands supported: 2600 MHz | 4G bands supported: 850 | 4G bands supported: 2500 MHz | 4G bands supported: 900 | Dynamic DNS (DDNS): Yes | 4G bands supported: 1800 | 4G bands supported: 1500 | DoS attack prevention: Yes | DMZ support: Yes | Port triggering: Yes | DHCP server: Yes | Firewall security: IPv4 SPI Firewall, IPv6 Firewall | 4G bands supported: 700 | 4G bands supported: 2300 | Depth: 190 mm | Supported network protocols: IPv4, IPv6 | WAN connection type: RJ-45 | USB port: No | 3G bands supported: 900 | 3G bands supported: 2100 MHz | 3G standards: HSPA | WLAN data transfer rate (first band): 574 Mbit/s | SIM card slot: Yes | 3G standards: UMTS | 3G bands supported: 850 | 3G standards: DC-HSDPA | Height: 99 mm | Product type: Tabletop router | Mobile network generation: 5G | Output current: 2 A | Detachable antenna(s): Yes | 4G bands supported: 3700 MHz | 4G bands supported: 3500 | Firewall: Yes | 4G bands supported: 2100 | 4G bands supported: 800 | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | 4G standard: LTE-TDD & LTE-FDD | Browser supported:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser | Wi-Fi Multimedia (WMM)/(WME): Yes | SIM card type: NanoSIM | On/off switch: Yes | WPS push button: Yes | Access Control List (ACL): Yes | Linux operating systems supported: Yes | Parental control: Yes | WLAN data transfer rate (second band): 1201 Mbit/s | Number of guest networks (2.4 GHz): 1 | Antenna design: Internal | Customs product code (TARIC): 8517620000 | Number of guest networks (5 GHz): 1 | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to water or moisture. | 5G bands supported: 700 | 5G bands supported: 1800 | 5G bands supported: 2300 | MU-MIMO technology: Yes | 5G bands supported: 3500 MHz | 5G bands supported: 2500 | 5G bands supported: 2100 | 5G bands supported: 3700 | 5G bands supported: 850 | Warnings: Do not expose the device to extreme temperatures. | 5G bands supported: 2600 | 5G bands supported: 800 | 5G bands supported: 900 MHz | Compliance certificates: RoHS | Compliance certificates: CE | Windows operating systems supported: Windows XP | Package weight: 1.19 kg | AC input frequency: 50/60 Hz | Ethernet LAN data rates: 100 Mbit/s | Ethernet LAN data rates: 1000 Mbit/s | Ethernet LAN data rates: 10 | Operating relative humidity (H-H): 10 - 90% | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 2000 | Windows operating systems supported: Windows 7 | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Windows operating systems supported: Windows 98SE | AC input voltage: 100 - 240 V | Security algorithms: 128-bit WEP | Networking standards: IEEE 802.11ax | Security algorithms: WPA | Windows operating systems supported: Windows 10 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Windows operating systems supported: Windows NT | Networking standards: IEEE 802.11ac | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 3 | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Security algorithms: WPA2-PSK | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Product colour: White | AC adapter included: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | DHCP client: Yes | Weight: 610 g | Reset button: Yes | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11b | Package width: 230 mm | Power source type: AC | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Wi-Fi standards: 802.11g | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11b | WLAN data transfer rate (max): 1800 Mbit/s | Package depth: 115 mm | Quick installation guide: Yes | Antennas quantity: 10 | Width: 99 mm | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Cables included: LAN (RJ-45) | Output voltage: 12 V | Ethernet LAN interface type: Gigabit Ethernet | Ethernet WAN: Yes | Mac operating systems supported: Yes | Package height: 221 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950