

TP-Link Archer MR202 wireless router Fast Ethernet Dual- band (2.4 GHz 5 GHz) 4G Black



Model: MR202

Manufacturer: TP-LINK

EAN: 8885020625745

Product Code: 606863

R1,967

Certification: CE, RoHS | Receiver sensitivity: 5 GHz: 11a 54M: -78 dBm 11ac VHT20: -92 dBm 11ac VHT20: -72 dBm 11ac VHT40: -90 dBm 11ac VHT40: -67 dBm 11ac VHT80: -87 dBm 11ac VHT80: -64 dBm 2,4 GHz: 11g 54M: -74 dBm 11n HT20: -91 dBm 11n HT20: -72 dBm 11n HT40: -88 dBm 11n HT40: -69 dBm | VPN support: PPTP VPN, OpenVPN | LED indicators: LAN, Power, WAN, WLAN | Ethernet LAN data rates: 10 | Reset button: Yes | Web-based management: Yes | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Ethernet LAN data rates: 100 Mbit/s | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11a | DHCP client: Yes | DC-in jack: Yes | Product colour: Black | Stateful Packet Inspection (SPI): Yes | Networking standards: IEEE 802.11b | Quick installation guide: Yes | AC adapter included: Yes | Quality of Service (QoS) support: Yes | 4G bands supported: 900 | 4G bands supported: 2100 | 4G bands supported: 800 | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 4G bands supported: 2600 MHz | 3G standards: UMTS | Guest

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

access: Yes | Windows operating systems supported: Windows 8 | Storage temperature (T-T): -40 - 60 °C | 4G bands supported: 1800 | Operating relative humidity (H-H): 10 - 90% | DHCP server: Yes | Transmit power: 20dBm(2.4G) 23dBm(5G) | Mac operating systems supported: Yes | Firewall security: IP and MAC Address Binding | Cabling technology: 10/100Base-T(X) | Port triggering: Yes | Height: 33.5 mm | Antenna design: External | WLAN data transfer rate (second band): 433 Mbit/s | Width: 174 mm | Security algorithms: WPA2-PSK | Point-to-point protocol over Ethernet (PPPoE): Yes | Wi-Fi standards: 802.11g | Ethernet LAN interface type: Fast Ethernet | 4G bands supported: 700 | Dynamic DNS (DDNS): Yes | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 | Wi-Fi standards: Wi-Fi 5 (802.11ac) | WLAN data transfer rate (max): 733 Mbit/s | Wi-Fi standards: 802.11b | Dynamic IP: Yes | Security algorithms: WPA | Security algorithms: 128-bit WEP | Windows operating systems supported: Windows NT | 3G standards: HSPA | DMZ support: Yes | Wi-Fi standards: 802.11a | Product type: Tabletop router | UMTS bands supported: 900 | Windows operating systems supported: Windows 7 | Output current: 1 A | Windows operating systems supported: Windows XP | UMTS bands supported: 2100 MHz | Mobile network generation: 4G | Port forwarding: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Plug and Play: Yes | Windows operating systems supported: Windows 10 | 3G/4G USB modem compatibility: No | Cables included: LAN (RJ-45) | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | UMTS bands supported: 850 | Windows operating systems supported: Windows 2000 | Ethernet LAN (RJ-45) ports: 3 | Firewall: Yes | Operating temperature (T-T): 0 - 40 °C | 3G: Yes | Antennas quantity: 2 | 4G bands supported: 2300 | Universal Plug and Play (UPnP): Yes | Static IP: Yes | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | 4G standard: LTE-TDD & LTE-FDD | Windows operating systems supported: Windows 98SE | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | 4G: Yes | Output voltage: 12 V | SIM card slot: Yes | 4G bands supported: 850 | 4G bands supported: 2500 MHz | Ethernet LAN: Yes | Depth: 124.5 mm | Supported network protocols: IPv4, IPv6 | Power source type: DC | Linux operating systems supported: Yes | DSL WAN: No | WLAN data transfer rate (first band): 300 Mbit/s | Memory card slot(s): No | Ethernet WAN: Yes | USB port: No | DoS attack prevention: Yes | WAN connection type: RJ-45 | Number of Ethernet LAN/WAN ports: 1 | Warnings: Do not expose the device to water or moisture. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to extreme temperatures.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950