

AMD Ryzen 5 8400F processor 4.2 GHz 16 MB L3 Tray



Model: 100-000001591

Manufacturer: AMD

EAN:

Product Code: 609581

R2,523

Compatible operating systems: Windows 10/11 x64, RHEL x86 64-bit, Ubuntu x86 64-bit | PCI Express slots version: 4.0 | Maximum number of PCI Express lanes: 20 | On-board graphics card model: Not available | Processor cache type: L3 | Processor model: 8400F | Discrete graphics card model: Not available | Processor cores: 6 | Discrete graphics card: No | On-board graphics card: No | Processor operating modes: 64-bit | Processor lithography: 4 nm | Processor family: AMD Ryzen™ 5 | Processor cache: 16 MB | Processor manufacturer: AMD | Processor threads: 12 | Memory channels: Dual-channel | Processor boost frequency: 4.7 GHz | Memory clock speeds supported by processor: 5200 | Memory clock speeds supported by processor: 3600 MHz | Processor socket: Socket AM5 | Thermal Design Power (TDP): 65 W | Configurable TDP-up: 65 W | Processor generation: AMD Ryzen 8000 Series | Processor base frequency: 4.2 GHz | Warnings: Use appropriate processor mounting equipment to avoid mechanical damage. | Warnings: Processors contain electronic components that may be harmful to the environment. Do not dispose of in the regular trash. | Supported instruction sets: AVX | Supported instruction sets: AVX-512 | USB ports quantity: 5 | Supported instruction sets: AVX 2.0 | Cooler included: No | Supported instruction sets: AES | Memory types supported by

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

processor: DDR5-SDRAM | Warnings: Processors can get very hot during operation. Make sure they are adequately cooled. | Supported instruction sets: SSE3 | Supported instruction sets: SSE | Market segment: Desktop | Supported instruction sets: SSE4.1 | Supported instruction sets: SSE2 | Configurable TDP-down: 45 W | Supported instruction sets: MMX

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950