

TP-Link 300Mbps Wireless N WiFi Router



Model: TL-WR841N/PL

Manufacturer: TP-LINK

EAN: 6935364091170

Product Code: 609779

R940

Certification: CE, FCC, RoHS | VPN support: PPTP, L2TP, IPSec | Antenna design: External | DHCP client: Yes | Package weight: 520 g | Windows operating systems supported: Windows 7 Home Basic | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Ethernet LAN data rates: 100 Mbit/s | Product colour: White | AC adapter included: Yes | Networking standards: IEEE 802.11b | Security algorithms: WPS | Package width: 288 mm | Windows operating systems supported: Windows Vista Home Basic x64 | Windows operating systems supported: Windows 7 Professional x64 | Filtering: Yes | Ethernet LAN data rates: 10 | Windows operating systems supported: Windows Vista Home Basic | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Windows operating systems supported: Windows Vista Business x64 | Windows operating systems supported: Windows XP Professional | Frequency band: 2.4 GHz | Windows operating systems supported: Windows Vista Enterprise x64 | Security algorithms: WPA | Product colour: Black | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Security algorithms: 128-bit WEP | Stateful Packet Inspection (SPI): Yes | Networking standards: IEEE 802.3 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Security algorithms: WPA2-PSK | Security algorithms: SSID | DC-in jack: Yes | Windows operating systems supported: Windows Vista Home Premium x64 | Windows operating systems supported: Windows XP Home x64 | Networking standards: IEEE 802.3u | Security algorithms: 152-bit WEP | Windows operating systems supported: Windows Vista Home Premium | Windows operating systems supported: Windows XP Home | Windows operating systems supported: Windows Vista Enterprise | Windows operating systems supported: Windows 7 Professional | Windows operating systems supported: Windows XP Professional x64 | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows Vista Ultimate x64 | Windows operating systems supported: Windows Vista Business | Windows operating systems supported: Windows Vista Ultimate | WLAN data transfer rates supported: 11 | Package height: 86 mm | Port forwarding: Yes | USB port: No | Dynamic DNS (DDNS): Yes | Windows operating systems supported: Windows 7 Home Premium | Reset button: Yes | Port triggering: Yes | Quick start guide: Yes | Weight: 700 g | Transmit power: 20 dBmW | Windows operating systems supported: Windows 7 Home Basic x64 | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Ethernet LAN (RJ-45) ports: 4 | WLAN data transfer rates supported: 300 Mbit/s | 3G: No | Antenna gain level (max): 5 dBi | Operating temperature (T-T): 0 - 40 °C | Wi-Fi standards: 802.11b | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | 4G: No | Windows operating systems supported: Windows 7 Starter x64 | Windows operating systems supported: Windows NT | WLAN data transfer rates supported: 54 | Windows operating systems supported: Windows 7 Enterprise x64 | Height: 28 mm | DMZ support: Yes | Ethernet LAN: Yes | SIM card slot: No | Depth: 119 mm | Firewall security: SPI | Ethernet WAN: Yes | VPN Passthrough: Yes | Rack mounting: No | DHCP server: Yes | xDSL connection: No | DSL WAN: No | Universal Plug and Play (UPnP): Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Firewall: Yes | Ethernet LAN interface type: Fast Ethernet | Package depth: 202 mm | Wi-Fi band: Single-band (2.4 GHz) | Windows operating systems supported: Windows 7 Enterprise | 3G/4G USB modem compatibility: No | Mobile network connection: No | Width: 174 mm | Detachable antenna(s): No | Windows operating systems supported: Windows 7 Starter | Product type: Tabletop router | Cabling technology: 10/100Base-T(X) | Windows operating systems supported: Windows 2000 Professional | Full duplex: Yes | Power consumption (typical): 8 W | Power source type: DC | Output voltage: 9 V | Windows operating systems supported: Windows 7 Ultimate x64 | Harmonized System (HS) code: 85176990 | Wi-Fi standards: 802.11g | LED indicators: Power, Status, WLAN | Input current: 0.6 A | Cables included: LAN (RJ-45) | Windows operating systems supported: Windows 7 Ultimate | Windows operating systems supported: Windows 2000 | Output current: 0.6 A | WLAN data transfer rate (max): 300 Mbit/s | On/off switch: Yes | DoS attack prevention: Yes | Filtering description: IP, MAC, URL | Mac operating systems supported: MacOS | Windows operating systems supported: Windows

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

98SE | Antennas quantity: 2 | Memory card slot(s): No | Linux operating systems supported: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950