

**NETGEAR
GS724TP
Managed
L2/L3/L4 Gigabit
Ethernet
(10/100/1000)
Power over
Ethernet (PoE)
Blue**



Model: GS724TP-300EUS

Manufacturer: NETGEAR

EAN: 606449162660

Product Code: 610155

R7,651

Certification: CE, FCC, VCCI, EN, C-Tick, CCC, CSA, UL/cUL, IEC | Link aggregation: Yes | Store-and-forward: Yes | Jumbo frames: 9216 | Spanning tree protocol: Yes | DHCP features: DHCP client | Fiber ethernet cabling technology: 1000BASE-SX | Port mirroring: Yes | Broadcast storm control: Yes | SSH/SSL support: Yes | IP routing: Yes | Switch type: Managed | Access Control List (ACL): Yes | Multicast support: Yes | Stackable: Yes | Number of queues: 8 | Switch layer: L2/L3/L4 | Fiber ethernet cabling technology: 1000BASE-LX | Number of static routes: 32 | Number of multicast

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

groups filtered: 128 | System event log: Yes | Management protocols: SNMP v1/v2/v3 | Flow control support: Yes | IGMP snooping: Yes | Warnings: Avoid contact of the device with liquid. | Warnings: Follow the safety guidelines for electrical current. | Warnings: Make sure the ventilation of the equipment is not blocked. | Width: 440 mm | Rack mounting: Yes | Power over Ethernet (PoE): Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | User guide: Yes | Product colour: Blue | 10G support: Yes | Power connector: DC-in jack | VLAN support: Yes | Noise level: 0 dB | Copper ethernet cabling technology: 1000BASE-T | Operating temperature (T-T): 0 - 50 °C | Manual: Yes | LED indicators: Speed | Packet buffer memory: 0.512 MB | Firmware upgradeable: Yes | Quick start guide: Yes | Networking standards: IEEE 802.1as | Number of fans: 3 fan(s) | Height: 43 mm | Storage temperature (T-T): -20 - 70 °C | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3ae | Quality of Service (QoS) support: Yes | Mean time between failures (MTBF): 634966 h | Operating altitude: 0 - 3000 m | Power consumption (max): 446.7 W | Number of VLANs: 64 | Networking standards: IEEE 802.1ab | Security algorithms: SSL/TLS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage relative humidity (H-H): 0 - 95% | Operating relative humidity (H-H): 0 - 90% | Networking standards: IEEE 802.3x | Copper ethernet cabling technology: 100BASE-TX | Full duplex: Yes | Depth: 204 mm | MAC address table: 8000 entries | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | LED indicators: Activity | Total Power over Ethernet (PoE) budget: 380 W | Switching capacity: 52 Gbit/s | Networking standards: IEEE 802.1p | Weight: 3.7 kg | AC input voltage: 100 - 240 V | LED indicators: Link | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: HTTPS | Security algorithms: 802.1x RADIUS | Power supply included: Yes | Networking standards: IEEE 802.1w | SFP module slots quantity: 2 | Jumbo frames support: Yes | Cables included: AC

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950