



**NETGEAR
GS728TP
Managed
L2/L3/L4 Gigabit
Ethernet
(10/100/1000)
Power over
Ethernet (PoE)
Grey**

Model: GS728TP-300EUS

Manufacturer: NETGEAR

EAN: 606449162257

Product Code: 610156

R8,170

Certification: CE, FCC Class A, RCM, ICES Class A, VCCI, KC, BSMI, UKCA | Warnings: Follow the safety guidelines for electrical current. | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid. | USB Type-A ports quantity: 1 | Networking standards: IEEE 802.1Q | Depth: 257 mm | Built-in processor: Yes | Height: 432 mm | Operating relative humidity (H-H): 0 - 90% | Width: 440 mm | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Processor manufacturer: ARM | Storage relative humidity (H-H):

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

0 - 95% | Processor model: ARM Cortex-A55 | Networking standards: IEEE 802.1D | Power source: AC
| Noise level: 26.8 dB | Power consumption (typical): 24 W | Networking standards: IEEE 802.3x |
Power over Ethernet (PoE) power per port: 190 W | Operating temperature (T-T): 0 - 50 °C | Weight:
3.78 kg | Power consumption (max): 226 W | Product colour: Grey | Storage temperature (T-T): -20 -
70 °C | Internal memory: 512 MB | Networking standards: IEEE 802.1w | Processor frequency: 800
MHz | Rack mounting: Yes | Power over Ethernet (PoE): Yes | Flash memory: 64 MB | VLAN support:
Yes | Number of fans: 2 fan(s) | Redundant fans support: Yes | Access Control List (ACL) IPv4 entries:
100 | DHCP features: DHCP snooping | Latency (10-100 Mbps): 8.864 µs | Latency (1 Gbps): 4.691 µs
| Port mirroring: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Number of multicast groups
filtered: 512 | MAC address table: 16000 entries | Switching capacity: 56 Gbit/s | Switch layer:
L2/L3/L4 | Power over Ethernet plus (PoE+) ports quantity: 24 | DHCP features: DHCPv6 client |
Number of VLANs: 256 | Packet buffer memory: 1.5 MB | Basic switching RJ-45 Ethernet ports type:
Gigabit Ethernet (10/100/1000) | IPv4 routes: 32 | Switch type: Managed | Access Control List (ACL):
Yes | Installed SFP modules quantity: 4 | ARP inspection: Yes | IPv6 routes: 32 | Mean time between
failures (MTBF): 1751613 h | Multicast support: Yes | Heat dissipation: 772.9 BTU/h

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950